



# TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 38 A - 72 V DC standard coil

LC1D386SD

! Discontinued on: 10 Oct 2020

(!) Discontinued

EAN Code: 3389110808445

#### Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-3 AC-1 AC-4
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] Rated Operational Current	50 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 38 A (at <60 °C) at <= 440 V AC AC-3 for power circuit
[Uc] Control Circuit Voltage	72 V DC

## Complementary

Motor Power Kw	18.5 kW at 500 V AC 50/60 Hz (AC-3) 18.5 kW at 660690 V AC 50/60 Hz (AC-3) 7.5 kW at 400 V AC 50/60 Hz (AC-4) 18.5 kW at 380400 V AC 50/60 Hz (AC-3) 9 kW at 220230 V AC 50/60 Hz (AC-3) 18.5 kW at 415440 V AC 50/60 Hz (AC-3)	
Motor Power Hp	10 hp at 230/240 V AC 50/60 Hz for 3 phases motors 10 hp at 200/208 V AC 50/60 Hz for 3 phases motors 5 hp at 240 V AC 50/60 Hz for 1 phase motors 20 hp at 480 V AC 50/60 Hz for 3 phases motors 25 hp at 600 V AC 50/60 Hz for 3 phases motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air Thermal Current	10 A (at 60 °C) for signalling circuit 50 A (at 60 °C) for power circuit	
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947	
Rated Breaking Capacity	550 A at 440 V for power circuit conforming to IEC 60947	

[Icw] Rated Short-Time Withstand Current	60 A 40 °C - 10 min for power circuit 430 A 40 °C - 1 s for power circuit 150 A 40 °C - 1 min for power circuit 310 A 40 °C - 10 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 63 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2 mOhm - Ith 50 A 50 Hz for power circuit
Power Dissipation Per Pole	5 W AC-1 3 W AC-3
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 690 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	30 Mcycles
Electrical Durability	1.4 Mcycles 50 A AC-1 at Ue <= 440 V 1.4 Mcycles 38 A AC-3 at Ue <= 440 V
Control Circuit Type	DC standard
Control Circuit Type  Coil Technology	DC standard  Built-in bidirectional peak limiting diode suppressor
Coil Technology	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC  0.71.25 Uc (-4060 °C):operational DC
Coil Technology  Control Circuit Voltage Limits	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC  0.71.25 Uc (-4060 °C):operational DC  11.25 Uc (6070 °C):operational DC
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant  Maximum Operating Rate	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm
Coil Technology Control Circuit Voltage Limits Inrush Power In W Hold-In Power Consumption In W Operating Time Time Constant Maximum Operating Rate Connections - Terminals	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm Power circuit: lugs-ring terminals - external diameter: 10 mm  Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5 Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver flat Ø 8 mm M4
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant  Maximum Operating Rate  Connections - Terminals  Tightening Torque	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm Power circuit: lugs-ring terminals - external diameter: 10 mm  Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5 Control circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver flat Ø 8 mm M4 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M4
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant  Maximum Operating Rate  Connections - Terminals  Tightening Torque  Auxiliary Contact Composition	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm Power circuit: lugs-ring terminals - external diameter: 10 mm  Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5 Control circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver flat Ø 8 mm M4 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M4  1 NO + 1 NC  type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant  Maximum Operating Rate  Connections - Terminals  Tightening Torque  Auxiliary Contact Composition  Auxiliary Contacts Type	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm Power circuit: lugs-ring terminals - external diameter: 10 mm  Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5 Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M4  1 NO + 1 NC  type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Coil Technology  Control Circuit Voltage Limits  Inrush Power In W  Hold-In Power Consumption In W  Operating Time  Time Constant  Maximum Operating Rate  Connections - Terminals  Tightening Torque  Auxiliary Contact Composition  Auxiliary Contacts Type  Signalling Circuit Frequency	Built-in bidirectional peak limiting diode suppressor  0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (6070 °C):operational DC 11.25 Uc (6070 °C):operational DC  5.4 W (at 20 °C)  5.4 W at 20 °C  20 ±20 % ms opening 63 ±15 % ms closing  28 ms  3600 cyc/h 60 °C  Control circuit: lugs-ring terminals - external diameter: 8 mm Power circuit: lugs-ring terminals - external diameter: 10 mm  Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5 Control circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M4  1 NO + 1 NC  type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1

Non-Overlap Time	<ul><li>1.5 ms on de-energisation between NC and NO contact</li><li>1.5 ms on energisation between NC and NO contact</li></ul>	
Mounting Support	Plate Rail	
Environment		
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1	

IEC 60947-4-1 IEC 60947-5-1 UL 508 **Product Certifications** GL DNV GOST RINA CSA BV LROS (Lloyds register of shipping) UL CCC **Ip Degree Of Protection** IP20 front face conforming to IEC 60529 **Protective Treatment** TH conforming to IEC 60068-2-30 **Climatic Withstand** conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat Permissible Ambient Air Temperature Around The Device -40...60 °C 60...70 °C with derating **Operating Altitude** 0...3000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94 **Mechanical Robustness** Vibrations contactor open (2 Gn, 5...300 Hz) Vibrations contactor closed (4 Gn, 5...300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (8 Gn for 11 ms) Height 85 mm Width 45 mm Depth 101 mm

## **Packing Units**

**Net Weight** 

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.3 cm
Package 1 Width	9.3 cm
Package 1 Length	5.2 cm
Package 1 Weight	604 g

0.54 kg

### **Contractual warranty**

Warranty 18 months

# Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc
<b>⊘</b>	Toxic Heavy Metal Free
<b>⊘</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information