# **Product datasheet**





### TeSys D contactor - 3P - <= 440 V - 38 A AC-3 - 24...60 V AC/DC coil

Local distributor code:

407811724 LC1D38BNE

EAN Code: 3606480987786

#### Main

Range	TeSys TeSys Deca
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Motor control
	Resistive load
Utilisation Category	AC-3
	AC-1
	AC-3e
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz
[le] Rated Operational Current	50 A (at <60 °C) at <= 440 V AC-1 for power circuit
	38 A (at <60 °C) at <= 440 V AC-3 for power circuit
	38 A (at <60 °C) at <= 440 V AC-3e for power circuit
[Uc] Control Circuit Voltage	2460 V AC 50/60 Hz
	2460 V DC

#### Complementary

Motor Power Kw	9 kW at 220230 V AC 50 Hz (AC-3)
	18.5 kW at 380400 V AC 50 Hz (AC-3)
	18.5 kW at 415 V AC 50 Hz (AC-3)
	18.5 kW at 440 V AC 50 Hz (AC-3)
	18.5 kW at 500 V AC 50 Hz (AC-3)
	18.5 kW at 660690 V AC 50 Hz (AC-3)
	9 kW at 220230 V AC 50 Hz (AC-3e)
	18.5 kW at 380400 V AC 50 Hz (AC-3e)
	18.5 kW at 415 V AC 50 Hz (AC-3e)
	18.5 kW at 440 V AC 50 Hz (AC-3e)
	18.5 kW at 500 V AC 50 Hz (AC-3e)
	18.5 kW at 660690 V AC 50 Hz (AC-3e)
Motor Power Hp	2 hp at 115 V AC 60 Hz for 1 phase motors
	5 hp at 230/240 V AC 60 Hz for 1 phase motors
	10 hp at 200/208 V AC 60 Hz for 3 phases motors
	10 hp at 230/240 V AC 60 Hz for 3 phases motors
	20 hp at 460/480 V AC 60 Hz for 3 phases motors
	25 hp at 575/600 V AC 60 Hz for 3 phases motors
Compatibility Code	LC1D
Pole Contact Composition	3 NO
Protective Cover	With
[Ith] Conventional Free Air	10 A (at 60 °C) for signalling circuit
Thermal Current	50 A (at 60 °C) for power circuit

Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
	550 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	550 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	100 A - 1 s for signalling circuit
Current	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
	60 A 40 °C - 10 min for power circuit
	·
	150 A 40 °C - 1 min for power circuit
	310 A 40 °C - 10 s for power circuit
	430 A 40 °C - 1 s for power circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
7.0000lated 1 doe 1 ating	
	63 A gG at <= 690 V coordination type 1 for power circuit
	63 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2 mOhm - Ith 50 A 50 Hz for power circuit
Power Dissipation Per Pole	5 W AC-1
	3 W AC-3
	3 W AC-3
	o w no oc
[Ui] Rated Insulation Voltage	Power circuit: 690 V conforming to IEC 60947-4-1
[e.j mateu meananen tenage	Signalling circuit: 690 V conforming to IEC 60947-1
	Signaling circuit. 696 V comorning to IEG 66547-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Safaty Poliability Layel	D404 = 4260062 avalage contactor with manning local conforming to ENVICO 42040 4
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
	13849-1
Mechanical Durability	
Mechanical Durability	15 Mcycles
	15 Mcycles
Mechanical Durability  Electrical Durability	15 Mcycles 1.8 Mcycles 35 A AC-3 at Ue <= 440 V
·	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V
·	15 Mcycles 1.8 Mcycles 35 A AC-3 at Ue <= 440 V
Electrical Durability	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V
	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V
Electrical Durability	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V
Electrical Durability  Control Circuit Type  Coil Technology	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting
Electrical Durability  Control Circuit Type	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC
Electrical Durability  Control Circuit Type  Coil Technology	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC
Electrical Durability  Control Circuit Type  Coil Technology	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC
Electrical Durability  Control Circuit Type  Coil Technology	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC
Electrical Durability  Control Circuit Type  Coil Technology	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (-4060 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC  15 VA 50/60 Hz (at 20 °C)  14 W (at 20 °C)  0.9 VA 50/60 Hz (at 20 °C)
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (6070 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC 15 VA 50/60 Hz (at 20 °C)  14 W (at 20 °C)  0.9 VA 50/60 Hz (at 20 °C)  0.6 W at 50/60 Hz
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (6070 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC  15 VA 50/60 Hz (at 20 °C)  14 W (at 20 °C)  0.9 VA 50/60 Hz (at 20 °C)  0.6 W at 50/60 Hz  4555 ms closing
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (6070 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC 15 VA 50/60 Hz (at 20 °C)  14 W (at 20 °C)  0.9 VA 50/60 Hz (at 20 °C)  0.6 W at 50/60 Hz
Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	1.8 Mcycles 35 A AC-3 at Ue <= 440 V 0.9 Mcycles 50 A AC-1 at Ue <= 440 V 1.8 Mcycles 35 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC 0.81.1 Uc (6070 °C):operational DC 11.1 Uc (6070 °C):operational AC/DC  15 VA 50/60 Hz (at 20 °C)  14 W (at 20 °C)  0.9 VA 50/60 Hz (at 20 °C)  0.6 W at 50/60 Hz  4555 ms closing

Connections - Terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid
	Power circuit: screw clamp terminals 1 2.510 mm <sup>2</sup> - cable stiffness: flexible without cable end
	Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: flexible without cable end
	Power circuit: screw clamp terminals 1 110 mm <sup>2</sup> - cable stiffness: flexible with cable end
	Power circuit: screw clamp terminals 2 1.56 mm² - cable stiffness: flexible with cable end
	Power circuit: screw clamp terminals 1 1.510 mm² - cable stiffness: solid Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: solid
Tightening Torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 M4
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 M3.5
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Plate Rail
Environment	
Standards	EN/IEC 60947-4-1
	EN/IEC 60947-5-1
	UL 60947-4-1 CSA C22.2 No 60947-4-1
	IEC 60335-1
Product Certifications	CCC CSA EAC
	UL
	KC
	DNV-GL LROS (Lloyds register of shipping)
	UKCA
Ip Degree Of Protection	IP20 front face conforming to IEC 60529
Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m

850 °C conforming to IEC 60695-2-1

Fire Resistance

Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (8 Gn for 11 ms)	
Height	85 mm	
Width	45 mm	
Depth	92 mm	
Net Weight	0.442 kg	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.200 cm
Package 1 Width	9.200 cm
Package 1 Length	11.200 cm
Package 1 Weight	458.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.168 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information