



## TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 115 A - coil 24 V DC

Local distributor code: 402840143

LC1F115BD

Discontinued on: 11 Jan 2023

! Discontinued

EAN Code: 3389110787986

#### Main

| Range                          | TeSys  |
|--------------------------------|--|
| Range Of Product               | TeSys F  |
| Product Or Component Type      | Contactor  |
| Device Short Name              | LC1F   |
| Contactor Application          | Resistive load<br>Motor control  |
| Utilisation Category           | AC-4<br>AC-1<br>AC-3   |
| Poles Description              | 3P   |
| [Ue] Rated Operational Voltage | <= 690 V AC 50/60 Hz<br><= 460 V DC                                      |
| [Uc] Control Circuit Voltage   | 24 V DC  |
| [le] Rated Operational Current | 200 A (at <40 °C) at <= 440 V AC-1<br>115 A (at <55 °C) at <= 440 V AC-3 |

### Complementary

| [Uimp] Rated Impulse Withstand Voltage         | 8 kV                                  |
|--|---------------------------------------|
| [Ith] Conventional Free Air<br>Thermal Current | 200 A (at 40 °C)                      |
| Rated Breaking Capacity                        | 920 A conforming to IEC 60947-4-1     |
| [Icw] Rated Short-Time Withstand               | 1100 A 40 °C - 10 s                   |
| Current  | 640 A 40 °C - 30 s                    |
|  | 520 A 40 °C - 1 min                   |
|  | 400 A 40 °C - 3 min                   |
|  | 320 A 40 °C - 10 min                  |
| Associated Fuse Rating                         | 125 A aM at <= 440 V                  |
|  | 200 A gG at <= 440 V                  |
| Average Impedance                              | 0.37 mOhm - Ith 200 A 50 Hz           |
| [Ui] Rated Insulation Voltage                  | 1000 V conforming to IEC 60947-4-1    |
|  | 1500 V conforming to VDE 0110 group C |
| Power Dissipation Per Pole                     | 15 W AC-1                             |
|  | 5 W AC-3                              |
| Overvoltage Category                           | III                                   |
| Power Pole Contact Composition                 | 3 NO                                  |

| Motor Power Kw   | 55 kW at 380400 V AC 50/60 Hz (AC-3)<br>59 kW at 415 V AC 50/60 Hz (AC-3)<br>59 kW at 440 V AC 50/60 Hz (AC-3)<br>75 kW at 500 V AC 50/60 Hz (AC-3)<br>80 kW at 660690 V AC 50/60 Hz (AC-3)<br>30 kW at 220230 V AC 50/60 Hz (AC-3)<br>18.5 kW at 400 V AC 50/60 Hz (AC-4)  |
|--|---|
| Control Circuit Voltage Limits                           | Operational: 0.851.1 Uc (at 55 °C)<br>Drop-out: 0.150.2 Uc (at 55 °C)   |
| Mechanical Durability                                    | 10 Mcycles  |
| Inrush Power In W  | 560 W (at 20 °C)  |
| Hold-In Power Consumption In W                           | 4.5 W at 20 °C  |
| Maximum Operating Rate                                   | 2400 cyc/h 55 °C  |
| Operating Time   | 3040 ms closing<br>3050 ms opening  |
| Connections - Terminals                                  | Power circuit: bar 2 cable(s) - busbar cross section: 20 x 3 mm  Power circuit: lugs-ring terminals 1 cable(s) 95 mm²  Power circuit: connector 1 cable(s) 95 mm²  Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²solid without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²solid without cable end Power circuit: bolted connection |
| Tightening Torque  | Power circuit: 10 N.m<br>Control circuit: 1.2 N.m   |
| Mounting Support   | Plate   |
| Heat Dissipation   | 4.5 W   |
| Standards  | IEC 60947-4-1<br>EN 60947-1<br>EN 60947-4-1<br>JIS C8201-4-1<br>IEC 60947-1   |
| Product Certifications                                   | CB ABS DNV CCC RINA BV UL LROS (Lloyds register of shipping) RMRoS UKCA   |
| Compatibility Code                                       | LC1F  |
| Control Circuit Type                                     | DC standard   |
| Environment  |   |
| Ip Degree Of Protection                                  | IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106  |
| Protective Treatment                                     | тн  |
| Ambient Air Temperature For Operation                    | -4060 °C  |
| Ambient Air Temperature For Storage                      | -6080 °C  |
| Permissible Ambient Air<br>Temperature Around The Device | 6070 °C at Uc   |
| Height   | 162 mm  |
| Width  | 163.3 mm  |

| Depth              | 171 mm                  |
|--------------------|-------------------------|
| Operating Altitude | 3000 m without derating |
| Net Weight         | 3 43 kg                 |

# **Packing Units**

| _                            |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 22.0 cm |
| Package 1 Width              | 19.5 cm |
| Package 1 Length             | 24.5 cm |
| Package 1 Weight             | 4.13 kg |

# **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information                         |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |

25 Apr 2024