

Product datasheet

TeSys K reversing contactor - 3P -AC-3 <= 440 V 9 A - 1 NC -220...230 VAC coil

LC2K09015M7

! Discontinued on: 10 Oct 2020

! Discontinued

EAN Code: 3389110492118

Main

Range	TeSys
Product Name	TeSys K
Product Or Component Type	Reversing contactor
Device Short Name	LC2K
Device Application	Control
Contactor Application	Resistive load Motor control
Utilisation Category	AC-1 AC-4 AC-3
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit: 690 V AC 50/60 Hz Signalling circuit: <= 690 V AC 50/60 Hz
[le] Rated Operational Current	20 A (at <50 °C) at <= 440 V AC AC-1 for power circuit 16 A (at <70 °C) at 690 V AC AC-1 for power circuit 9 A at <= 440 V AC AC-3 for power circuit
Motor Power Kw	2.2 kW at 220230 V AC 50/60 Hz 4 kW at 380415 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 4 kW at 480 V AC 50/60 Hz 4 kW at 500600 V AC 50/60 Hz 4 kW at 660690 V AC 50/60 Hz
Control Circuit Type	AC at 50/60 Hz
[Uc] Control Circuit Voltage	220230 V AC 50/60 Hz
Auxiliary Contact Composition	1 NC
[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	20 A (at 50 °C) for power circuit 10 A (at 50 °C) for signalling circuit
Irms Rated Making Capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947

Rated Breaking Capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220230 V conforming to IEC 60947 110 A at 380400 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	90 A 50 °C - 1 s for power circuit 85 A 50 °C - 5 s for power circuit 80 A 50 °C - 10 s for power circuit 60 A 50 °C - 10 s for power circuit 45 A 50 °C - 30 s for power circuit 40 A 50 °C - 3 min for power circuit 40 A 50 °C - 3 min for power circuit 80 A - 1 s for signalling circuit 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit 20 A 50 °C - >= 15 min for power circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit 25 A aM for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit: 600 V conforming to UL 508 Power circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-5-1 Signalling circuit: 600 V conforming to UL 508 Power circuit: 600 V conforming to CSA C22.2 No 14 Signalling circuit: 600 V conforming to CSA C22.2 No 14
Electrical Durability	0.18 Mcycles 20 A AC-1 at Ue <= 440 V 1.3 Mcycles 9 A AC-3 at Ue <= 440 V
Interlocking Type	Mechanical
Mounting Support	Rail Plate
Standards	EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1
Product Certifications	CB Scheme CCC UL CSA EAC CE UKCA
Connections - Terminals	Solder pins - busbar cross section: 1.5 x 0.9 mm
Operating Time	1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	5 Mcycles
Maximum Operating Rate	3600 cyc/h
Complementary	
Control Circuit Voltage Limits	Operational: 0.81.15 Uc (at <50 °C) Drop-out: 0.20.75 Uc (at <50 °C)
Inrush Power In Va	30 VA (at 20 °C)
Hold-In Power Consumption In Va	4.5 VA (at 20 °C)
Heat Dissipation	1.3 W

Auxiliary Contacts Type	type instantaneous 1 NC	
Signalling Circuit Frequency	<= 400 Hz	
Minimum Switching Current	5 mA for signalling circuit	
Minimum Switching Voltage	17 V for signalling circuit	
Non Overlap Distance	0.5 mm	
Insulation Resistance	> 10 MOhm for signalling circuit	

Environment

Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2. Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2. Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2. Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2.			
TC conforming to DIN 50016 -2550 °C Toperation -5080 °C -5080 °C Toperating Altitude Toperating Altitude Toperating Altitude Toperating Altitude Toperating Altitude Toperating to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 Toperating Altitude Toperating Altitude Toperating to UL 94 Requirement 2 conforming to NF F 16-102 Toperating to NF F 16-101 Toper	Ip Degree Of Protection	IP20 conforming to VDE 0106	
Operation Ambient Air Temperature For Storage Operating Altitude Flame Retardance V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 Mechanical Robustness Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6	Protective Treatment	· · · · · · · · · · · · · · · · · · ·	
Storage Operating Altitude 2000 m without derating V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 Mechanical Robustness Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6		-2550 °C	
Flame Retardance V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 Mechanical Robustness Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6	•	-5080 °C	
Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 Mechanical Robustness Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6	Operating Altitude	2000 m without derating	
Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6	Flame Retardance	Requirement 2 conforming to NF F 16-101	
Height 58 mm	Mechanical Robustness	,	
	Height	58 mm	
Width 90 mm	Width	90 mm	
Depth 57 mm	Depth	57 mm	
Net Weight 0.39 kg	Net Weight	0.39 kg	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6 cm
Package 1 Width	6.2 cm
Package 1 Length	9.2 cm
Package 1 Weight	430 g

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information