Product datasheet





TeSys D - star delta starter - 3 x 3P (3 NO) - 80 A - 230 V AC coil

Local distributor code:

402923523

LC3D80P7A64

! Discontinued on: 9 Feb 2023

EAN Code: 3389110961393

! Discontinued

Main

Range	TeSys	
Product Name	TeSys Deca	
Product Or Component Type	Star delta starter	
Device Short Name	LC3D	
Contactor Application	Motor control	
Utilisation Category	AC-3	
Device Presentation	Pre-wired	
Poles Description	3 x 3P	
Power Pole Contact Composition	Composition 3 x 3 NO	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz	
e] Rated Operational Current 80 A (at <60 °C) at <= 440 V AC AC-3 for power circuit		
Motor Power Kw	37 kW at 220/230 V AC 50/60 Hz 75 kW at 380/400 V AC 50/60 Hz 75 kW at 415 V AC 50/60 Hz 75 kW at 440 V AC 50/60 Hz	
Control Circuit Type	AC at 50/60 Hz	
[Uc] Control Circuit Voltage	230 V AC 50/60 Hz	
Auxiliary Contact Composition	1 NC for KM2 line contactor 1 NO for KM3 delta contactor	
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947	
Overvoltage Category	III	
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 1000 V conforming to IEC 60947-1	
Electrical Durability	10 Mcycles 80 A AC-3 at Ue <= 440 V	
Interlocking Type	Mechanical	
Mounting Support	Plate	
Standards	EN 60947-4-1 IEC 60947-4-1 EN 60947-5-1 UL 508 IEC 60947-5-1 CSA C22.2 No 14	

Product Certifications	RINA
	GL
	UL
	LROS (Lloyds register of shipping)
	DNV
	CCC
	GOST
	BV
	CSA

Complementary

•		
Connections - Terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end	
	Power circuit: screw clamp terminals 1 450 mm² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 2 425 mm² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 1 450 mm ² - cable stiffness: flexible with cable end	
	Power circuit: screw clamp terminals 2 416 mm² - cable stiffness: flexible with cable end	
	Power circuit: screw clamp terminals 1 450 mm² - cable stiffness: solid without cable end	
	Power circuit: screw clamp terminals 2 425 mm ² - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end	
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on screw clamp terminals - with screwdriver flat Ø 68 mm	
Mechanical Durability	4 Mcycles	
Maximum Operating Rate	30 cyc/h 60 °C	
Starting Time	30 s	
Coil Technology	Without built-in suppressor module	
Control Circuit Voltage Limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <55 °C) Operational: 0.81.1 Uc at 50 Hz (at <55 °C) Operational: 0.851.1 Uc at 60 Hz (at <55 °C)	
Inrush Power In Va	140 VA 60 Hz cos phi 0.75 (at 20 °C) 160 VA 50 Hz cos phi 0.75 (at 20 °C)	
Hold-In Power Consumption In Va	13 VA 60 Hz cos phi 0.3 (at 20 °C) 15 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat Dissipation	45 W at 50/60 Hz	
Auxiliary Contacts Type	Mechanically linked conforming to IEC 60947-5-1 3 x 1 NO + 1 NC Mirror contact conforming to IEC 60947-4-1 3 x 1 NC	
Signalling Circuit Frequency	25400 Hz	
Minimum Switching Current	5 mA for signalling circuit	
	17 V for signalling circuit	
Minimum Switching Voltage	17 V for signaling circuit	
Minimum Switching Voltage Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
	1.5 ms on de-energisation between NC and NO contact	
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	

Net Weight 5.4 kg

Environment

Insulation Resistance	> 10 MOhm for signalling circuit	
Ip Degree Of Protection	IP20 front face conforming to IEC 60529	
Protective Treatment	TH conforming to IEC 60068-2-30	
Pollution Degree	3	
Ambient Air Temperature For Storage	-6080 °C	
Ambient Air Temperature For Operation	-4060 °C 6070 °C with derating	
Operating Altitude	3000 m	
Fire Resistance	850 °C conforming to IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz Shocks contactor open: 8 Gn for 11 ms Vibrations contactor closed: 3 Gn, 5300 Hz Shocks contactor closed: 10 Gn for 11 ms	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	28.0 cm
Package 1 Width	23.0 cm
Package 1 Length	41.0 cm
Package 1 Weight	6.54 kg

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information Yes	
Ø	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations
	Circularity Profile

2 May 2024