Product datasheet





TeSys D contactor - 4P(4 NO) -AC-1 - <= 440 V 125 A - 48 V DC coil

Local distributor code:

402942892 LP1D80004ED

EAN Code: 3389110203448

Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LP1D
Contactor Application	Resistive load
Utilisation Category	AC-1 AC-3 AC-3e AC-4
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] Rated Operational Current	125 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3e for power circuit 55 A (at <60 °C) at <= 400 V AC AC-4 for power circuit
[Uc] Control Circuit Voltage	48 V DC

Complementary

Compatibility Code	LP1D
Pole Contact Composition	4 NO
Protective Cover	Without
[Ith] Conventional Free Air Thermal Current	125 A (at 60 °C) for power circuit
Irms Rated Making Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	135 A 40 °C - 10 min for power circuit 320 A 40 °C - 1 min for power circuit 640 A 40 °C - 10 s for power circuit 990 A 40 °C - 1 s for power circuit
Associated Fuse Rating	200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit
Power Dissipation Per Pole	12.5 W AC-1
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1
Overvoltage Category	III

Life Is On Schneider 20 Apr 2024

Safety Reliability Level	Pollution Degree	3
Bilda = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1		8 kV conforming to IEC 60947
Electrical Durability 0.8 Mcycles 125 A AC-1 at Ue <= 440 V Control Circuit Type DC DC standard Coll Technology Without built-in suppressor module Control Circuit Voltage Limits 0.1.0.3 Mc; 4070 "C) drop-out DC 0.851.1 Uc (4055 "C) operational DC 11.1 Uc (5570 "C) operational DC 11 Uc (5570 "C) operationa	Safety Reliability Level	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Control Circuit Type DC DC standard Coil Technology Without built-in suppressor module Control Circuit Voltage Limits 0.10.3 Uc (-4070 °C)c/drop-out DC 0.851.1 Uc (-4055 °C) operational DC 11.1 Uc (5570 °C)coperational DC 11 Uc (5570 °	Mechanical Durability	4 Mcycles
Coil Technology Without built-in suppressor module Control Circuit Voltage Limits 0.10.3 Uc (-4070 °C)/drop-out DC 0.881.1 Uc (-4055 °C)/operational DC 11.1 Uc (5570 °C) 11.1 Uc (5570 °C)/operational DC 11.1 Uc (5570 °C) 11.1 Uc (5570 °C)/operational DC 11.1 Uc (5570 °C) Inrush Power In W 22 W (at 20 °C) Porating Time 235 ms closing Time Constant 75 ms Maximum Operating Rate 3600 cyc/h 60 °C Connections - Terminals Control circuit: screw clamp terminals 1.14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Power circuit: connector 2.425 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2.14 mm² - cable stiffness: solid Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with Cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2.425 mm² - cable stiffness: f	Electrical Durability	0.8 Mcycles 125 A AC-1 at Ue <= 440 V
Control Circuit Voltage Limits 0.10.3 Uc (-4070 °C) drop-out DC 0.881.1 Uc (-4055 °C) operational DC 11.1 Uc (-5055 °C) operational DC 11 Uc (-5055 °C	Control Circuit Type	DC DC standard
Inrush Power In W 22 W (at 20 °C) Hold-In Power Consumption In W 22 W (at 20 °C) Operating Time 620 ms opening 2035 ms closing Time Constant 75 ms Maximum Operating Rate Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Power circuit: connector 4 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Control circuit: connector 1 450 mm² - cable stiffness: solid Control circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: solid Control circuit: connector 2 416 mm² - cable stiffness: solid Control circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: fl	Coil Technology	Without built-in suppressor module
Hold-In Power Consumption In W 22 W at 20 °C Operating Time 620 ms opening 2035 ms closing Time Constant 75 ms Maximum Operating Rate 3800 cyc/h 60 °C Connections - Terminals Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 125 mm² - cable stiffness: solid Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 2 425 mm² - cable stiffness: solid Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Tightening Torque Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.2 N.m - on connector has screw hard Ø 6 to Ø 8 mm Power circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 Mounting Support Rail Plate Environment Standards CSA C22 No 14 EN 60947-6-1 IEC 60947-6-1 I	Control Circuit Voltage Limits	0.851.1 Uc (-4055 °C):operational DC
Time Constant 75 ms	Inrush Power In W	22 W (at 20 °C)
Time Constant 75 ms Maximum Operating Rate 3600 cyc/h 60 °C Connections - Terminals Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 12,5 mm² - cable stiffness: flexible with cable end Power circuit: 12 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 12 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 12 N.m - on	Hold-In Power Consumption In W	22 W at 20 °C
Maximum Operating Rate Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: 1.2 nm - on screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Control circuit: 1.2 nm - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 nm - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 nm - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 nm - on connector hexagonal screw head 4 mm Control circuit: 1.2 nm - on connector hexagonal screw head 4 mm Control circuit: 1.2 nm - on lugs-ring terminals - with screwdriver pozidriv No 2 Mounting Support Rail Plate Environment Standards CSA C22.2 No 14 EN 60947-6-1 IEC 60947-5-1 UL 508 Product Certifications By CCC CSA DNV EAC GL CLCC CSA DNV EAC GL LROS (Lloyds register of shipping)	Operating Time	
Connections - Terminals Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Tightening Torque Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 Mounting Support Rail Plate Environment Standards CSA C22.2 No 14 EN 60947-5-1 UL 508 Product Certifications By CCC CSA DNV EAC GL LROS (Lloyds register of shipping)	Time Constant	75 ms
cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on connector - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 Mounting Support Rail Plate Environment Standards CSA C22.2 No 14 EN 60947-4-1 EC 60947-5-1 UL 508 Product Certifications BV CCC CSA DNV EAC GL LROS (Lloyds register of shipping)	Maximum Operating Rate	3600 cyc/h 60 °C
Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 Mounting Support Rail Plate CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-4-1 UL 508 Product Certifications BV CCC CSA DNV EAC GL LROS (Lloyds register of shipping)	Connections - Terminals	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 2 425 mm² - cable stiffness: solid Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with
Plate	Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm
EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 Product Certifications BV CCC CSA DNV EAC GL LROS (Lloyds register of shipping)		
CCC CSA DNV EAC GL LROS (Lloyds register of shipping)	Standards	EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1
UL UKCA Ip Degree Of Protection IP20 front face conforming to IEC 60529		CCC CSA DNV EAC GL LROS (Lloyds register of shipping) UL UKCA

Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (8 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)
Height	127 mm
Width	96 mm
Depth	181 mm
Net Weight	2.685 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	14.000 cm
Package 1 Length	21.000 cm
Package 1 Weight	2.619 kg
Unit Type Of Package 2	S02
Number Of Units In Package 2	2
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.499 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	32
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	95.978 kg

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

9	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
⊘	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations