# **Product datasheet**

Specification





# TeSys LRD thermal overload relays - 16...24 A - class 10A

Local distributor code:

402959018 LRD223

EAN Code: 3389110822427

#### Main

| Range                               | TeSys<br>TeSys Deca   |
|-------------------------------------|---|
| Product Name                        | TeSys LRD<br>TeSys Deca   |
| Product Or Component Type           | Differential thermal overload relay   |
| Device Short Name                   | LRD   |
| Relay Application                   | Motor protection  |
| Product Compatibility               | LC1D25<br>LC1D32<br>LC1D38  |
| Network Type                        | AC<br>DC  |
| Thermal Overload Class              | Class 10A conforming to IEC 60947-4-1   |
| Thermal Protection Adjustment Range | 1624 A  |
| [Ui] Rated Insulation Voltage       | Power circuit: 600 V conforming to CSA  Power circuit: 600 V conforming to UL  Power circuit: 690 V conforming to IEC 60947-4-1 |

#### Complementary

| Network Frequency                              | 0400 Hz  |
|--|--|
| Mounting Support                               | Plate, with specific accessories Rail, with specific accessories Under contactor           |
| Tripping Threshold                             | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1   |
| Auxiliary Contact Composition                  | 1 NO + 1 NC  |
| [Ith] Conventional Free Air<br>Thermal Current | 5 A for signalling circuit   |
| Permissible Current                            | 1.5 A at 240 V AC-15 for signalling circuit<br>0.1 A at 250 V DC-13 for signalling circuit |
| [Ue] Rated Operational Voltage                 | 690 V AC 0400 Hz for power circuit conforming to IEC 60947-4-1                             |
| Associated Fuse Rating                         | 4 A gG for signalling circuit 4 A BS for signalling circuit                                |
| [Uimp] Rated Impulse Withstand Voltage         | 6 kV   |
| Phase Failure Sensitivity                      | Tripping current 130 % of Ir on two phase, the last one at 0                               |
| Control Type                                   | Red push-button: stop<br>Blue push-button: reset   |
| Temperature Compensation                       | -2060 °C   |

| Connections - Terminals | Control circuit: spring terminals 1 cable(s) 12.5 mm² solid without cable end Control circuit: spring terminals 1 cable(s) 12.5 mm² flexible without cable end Power circuit: spring terminals 1 cable(s) 1.54 mm² flexible without cable end Power circuit: spring terminals 1 cable(s) 1.54 mm² flexible with cable end |
|-------------------------|---|
| Height                  | 93 mm   |
| Width                   | 45 mm   |
| Depth                   | 72 mm   |
| Net Weight              | 0.14 kg   |

#### **Environment**

| Climatic Withstand                    | conforming to IACS E10   |
|---------------------------------------|--|
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |
| Ambient Air Temperature For Operation | -2060 °C without derating conforming to IEC 60947-4-1  |
| Ambient Air Temperature For Storage   | -6070 °C   |
| Flame Retardance                      | V1 conforming to UL 94   |
| Mechanical Robustness                 | Vibrations: 6 Gn conforming to IEC 60068-2-6<br>Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7  |
| Dielectric Strength                   | 1.89 kV at 50 Hz conforming to IEC 60947-1   |
| Standards                             | EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495 |
| Product Certifications                | IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA  |

### **Packing Units**

| PCE       |
|-----------|
| 1         |
| 5.500 cm  |
| 8.000 cm  |
| 10.000 cm |
| 196.300 g |
| S02       |
| 23        |
| 15.000 cm |
| 30.000 cm |
| 40.000 cm |
| 4.758 kg  |
|           |

| Unit Type Of Package 3       | P06       |
|------------------------------|-----------|
| Number Of Units In Package 3 | 368       |
| Package 3 Height             | 75.000 cm |
| Package 3 Width              | 80.000 cm |
| Package 3 Length             | 60.000 cm |
| Package 3 Weight             | 84.130 kg |

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information                         |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |