# **Product datasheet**

Specifications





# TeSys LRD thermal overload relays - 80...104 A - class 10A

Local distributor code:

381829609 LRD33656

EAN Code: 3389110520088

#### Main

| Range                               | TeSys  |  |
|-------------------------------------|--|--|
| Product Name                        | TeSys LRD  |  |
|                                     | TeSys Deca                                       |  |
| Product Or Component Type           | Differential thermal overload relay              |  |
| Device Short Name                   | LRD  |  |
| Relay Application                   | Motor protection                                 |  |
| Product Compatibility               | LC1D95   |  |
|                                     | LC1D80   |  |
| Network Type                        | DC   |  |
|                                     | AC   |  |
| Thermal Overload Class              | Class 10A conforming to IEC 60947-4-1            |  |
| Thermal Protection Adjustment Range | 80104 A  |  |
| [Ui] Rated Insulation Voltage       | Power circuit: 600 V conforming to CSA           |  |
|                                     | Power circuit: 600 V conforming to UL            |  |
|                                     | Power circuit: 750 V conforming to IEC 60947-4-1 |  |

### Complementary

| Network Frequency 0400 Hz                      |  |  |
|--|--|--|
| Mounting Support                               | Plate<br>Rail  |  |
| Tripping Threshold                             | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1   |  |
| Auxiliary Contact Composition                  | 1 NO + 1 NC  |  |
| [Ith] Conventional Free Air<br>Thermal Current | 5 A for signalling circuit   |  |
| Permissible Current                            | 0.72 A at 500 V AC-15 for signalling circuit<br>0.06 A at 440 V DC-13 for signalling circuit |  |
| [Ue] Rated Operational Voltage                 | 1000 V AC 0400 Hz for power circuit conforming to IEC 60947-4-1                              |  |
| Associated Fuse Rating                         | 4 A gG for signalling circuit<br>4 A BS for signalling circuit                               |  |
| [Uimp] Rated Impulse Withstand Voltage         | 6 kV   |  |
| Phase Failure Sensitivity                      | Tripping current 130 % of Ir on two phase, the last one at 0                                 |  |
| Control Type                                   | Red push-button: stop<br>Blue push-button: reset   |  |
| Temperature Compensation                       | -2060 °C   |  |

| Connections - Terminals | Power circuit: screw clamp terminals 1 cable(s) 435 mm² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 435 mm² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 435 mm² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm² solid without cable end |
|-------------------------|--|
| Tightening Torque       | Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 9 N.m - on screw clamp terminals  |
| Height                  | 123 mm   |
| Net Weight              | 1 kg   |

## **Environment**

| Ziivii oiiiiiciit                     |  |  |
|---------------------------------------|--|--|
| Climatic Withstand                    | conforming to IACS E10   |  |
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |  |
| Ambient Air Temperature For Operation | -2060 °C without derating conforming to IEC 60947-4-1  |  |
| Ambient Air Temperature For Storage   | -6070 °C   |  |
| Flame Retardance                      | V1 conforming to UL 94   |  |
| Mechanical Robustness                 | Vibrations: 6 Gn conforming to IEC 60068-2-6<br>Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7  |  |
| Dielectric Strength                   | 2.2 kV at 50 Hz conforming to IEC 60947-1  |  |
| Standards                             | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1<br>GB/T 14048.4<br>GB/T 14048.5<br>EN 50495 |  |
| Product Certifications                | IEC UL CSA CCC EAC ATEX INERIS UKCA  |  |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 20.0 cm  |
| Package 1 Width              | 13.55 cm |
| Package 1 Length             | 10.25 cm |
| Package 1 Weight             | 1.015 kg |

## **Contractual warranty**

| warranty 18 months |
|--------------------|
|--------------------|



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>Ø</b> | Toxic Heavy Metal Free     |     |
| <b>⊘</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |