# **Product datasheet**

Specifications





# Advanced control unit, TeSys U, 4.5-18A, 1P motors, protection & diagnostic, class 10, coil 24V DC

Local distributor code: 389810814 LUCC18BL

EAN Code: 3389110364507

#### Main

| Mani                                 |  |
|--------------------------------------|--|
| Range                                | TeSys  |
| Range Of Product                     | TeSys Ultra  |
| Product Name                         | TeSys Ultra  |
| Device Short Name                    | LUCC   |
| Product Or Component Type            | Advanced control unit  |
| Device Application                   | Motor control<br>Motor protection  |
| Product Specific Application         | Basic protection and advanced functions, communication   |
| Main Function Available              | Manual reset Earth fault protection Protection against phase failure and phase imbalance Protection against overload and short-circuit   |
| Product Compatibility                | Power base LUB32 Power base LUB38 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B32BL Reversing contactor breaker LU2B38BL  |
| [Ue] Rated Operational Voltage       | 690 V AC   |
| Network Frequency                    | 4060 Hz  |
| Load Type                            | Single-phase motor   |
| Utilisation Category                 | AC-44<br>AC-43<br>AC-41  |
| Motor Power Kw                       | 4 kW at 400440 V AC 50/60 Hz for 1 phase motors  |
| Rated Motor Current Adjustment Range | 4.518 A  |
| Thermal Overload Class               | Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to IEC 60947-6-2 Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to UL 508 |
| Tripping Threshold                   | 14.2 x Ir +/- 20 %   |
| [Uc] Control Circuit Voltage         | 24 V DC  |

#### Complementary

| Control Circuit Voltage Limits | 2027 V for DC circuit 24 V in operation<br>14.5 V for DC circuit 24 V drop-out  |
|--------------------------------|---|
| Typical Current Consumption    | 220 mA at 24 V DC I maximum while closing with LUB32 220 mA at 24 V DC I maximum while closing with LUB38 80 mA at 24 V DC I rms sealed with LUB32 80 mA at 24 V DC I rms sealed with LUB38 |

12 May 2024 Life Is On Schneider

| Heat Dissipation                          | 0.000  |  |
|---|--|--|
| Heat Dissipation                          | 3 W for control circuit with LUB32   |  |
|   | 3 W for control circuit with LUB38   |  |
| Operating Time                            | 35 ms opening with LUB32 for control circuit   |  |
|   | 35 ms opening with LUB38 for control circuit   |  |
|   | 70 ms closing with LUB32 for control circuit   |  |
|   | 70 ms closing with LUB38 for control circuit   |  |
| Reset                                     | Manual reset   |  |
| Standards                                 | EN 60947-6-2   |  |
|   | IEC 60947-6-2  |  |
|   | UL 60947-4-1, with phase barrier   |  |
|   | CSA C22.2 No 60947-4-1, with phase barrier   |  |
|   | Co.  |  |
| Product Certifications                    | CE   |  |
|   | UL   |  |
|   | CSA  |  |
|   | CCC  |  |
|   | EAC  |  |
|   | ASEFA  |  |
|   | ATEX   |  |
|   | Marine   |  |
| [Ui] Rated Insulation Voltage             | 690 V conforming to IEC 60947-6-2  |  |
|   | 600 V conforming to UL 60947-4-1   |  |
|   | 600 V conforming to CSA C22.2 No 60947-4-1   |  |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kV conforming to IEC 60947-6-2   |  |
| Safe Separation Of Circuit                | 400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1        |  |
| care coparation or circuit                | 400 V SELV between the control or auxiliary circuit and the main circuit conforming to |  |
|   | IEC 60947-1  |  |
| Fixing Mode                               | Plug-in (front face)   |  |
| Width                                     | 45 mm  |  |
| Height                                    | 66 mm  |  |
| Depth                                     | 60 mm  |  |
| Compatibility Code                        | LUCC   |  |
| Environment                               |  |  |
|   | ID00 front people and using terminals conferminate ID0 00047.4                         |  |
| Ip Degree Of Protection                   | IP20 front panel and wired terminals conforming to IEC 60947-1                         |  |
|   | IP20 other faces conforming to IEC 60947-1   |  |
|   | IP40 front panel outside connection zone conforming to IEC 60947-1                     |  |
| Protective Treatment                      | TH conforming to IEC 60068   |  |

| Ip Degree Of Protection                  | IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP40 front panel outside connection zone conforming to IEC 60947-1 |
|--|--|
| Protective Treatment                     | TH conforming to IEC 60068   |
| Ambient Air Temperature For Operation    | -2570 °C   |
| Ambient Air Temperature For Storage      | -4085 °C   |
| Operating Altitude                       | 2000 m   |
| Fire Resistance                          | 960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12   |
| Shock Resistance                         | 10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27  |
| Vibration Resistance                     | 2 gn, 5300 Hz, power poles open conforming to IEC 60068-2-6<br>4 gn, 5300 Hz, power poles closed conforming to IEC 60068-2-6   |
| Resistance To Electrostatic<br>Discharge | 8 kV level 3 in open air conforming to IEC 61000-4-2<br>8 kV level 4 on contact conforming to IEC 61000-4-2  |
| Resistance To Radiated Fields            | 10 V/m 3 conforming to IEC 61000-4-3   |
| Resistance To Fast Transients            | 2 kV class 3 serial link conforming to IEC 61000-4-4<br>4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4   |
| Immunity To Radioelectric Fields         | 10 V conforming to IEC 61000-4-6   |
| Immunity To Microbreaks                  | 3 ms   |
| •  |  |

| Immunity To Voltage Dips | 70 % / 500 ms conforming to IEC 61000-4-11 |  |
|--------------------------|--|--|

### **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 5.000 cm  |
| Package 1 Width              | 8.100 cm  |
| Package 1 Length             | 8.700 cm  |
| Package 1 Weight             | 123.000 g |
| Unit Type Of Package 2       | S02       |
| Number Of Units In Package 2 | 23        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 3.124 kg  |

# **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Mercury Free                       |
|----------|------------------------------------|
| <b>Ø</b> | Rohs Exemption Information Yes     |
| <b>Ø</b> | Pvc Free                           |
| <b>②</b> | Halogen Free Plastic Parts Product |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information                         |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |