

Product datasheet

Specifications



devicenet communication module - for TeSys U - 24 V DC

Local distributor code:

393517970

LULC09

⚠ Discontinued on: 10 Apr 2024

EAN Code: 3389119409759

⚠ To be discontinued

Main

Range	TeSys
Device Short Name	LUL
Product Or Component Type	Communication module
Product Compatibility	LUCB LUCM LUCA LUCD LUCL LUCC
Device Application	Communication
Range Compatibility	TeSys TeSys U LUB non reversing power base TeSys TeSys U LU2B reversing power base

Complementary

Main Function Available	Communication module
Mounting Mode	Plug-in
Mounting Location	Front side
Physical Interface	Open style connector
Bus Type	DeviceNet
Communication Port Protocol	CAN2.0A CAN2.B
Addressing	0...63
Current Consumption	1.5 mA at 24 V DC 20...28 V
Logic Input	Positive at 24 V DC - 7 mA
Response Time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input Type	Resistive
Number Of Outputs	2 dedicated to starter-controller coil operation 1
[Us] Rated Supply Voltage	24 V DC
Output Current	<= 500 mA
Protection Type	GL fuse 2 A
Switching Current Capacity	0.5 mA at 24 V
Local Signalling	3 LEDs front panel

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connection Pitch	5 mm open style DeviceNet 3.81 mm
Connections - Terminals	Screw clamp terminals 1 cable(s) 0.14...1 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.14...1 mm²rigid without cable end Screw clamp terminals 1 cable(s) 0.25...0.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 0.25...1 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.14...0.5 mm²rigid without cable end Screw clamp terminals 2 cable(s) 0.14...0.75 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.25...0.34 mm²flexible with cable end BUS 1 cable(s) 0.2...2.5 mm²flexible without cable end BUS 1 cable(s) 0.2...2.5 mm²rigid without cable end BUS 1 cable(s) 0.25...2.5 mm²flexible with cable end BUS 2 cable(s) 0.14...0.5 mm²rigid without cable end BUS 2 cable(s) 0.25...1 mm²flexible with cable end BUS 2 cable(s) 0.5...1.5 mm²flexible with cable end BUS 2 cable(s) 0.5...1.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.75 mm²flexible with cable end
Associated Cable Type	AWG 26...AWG 16 for screw clamp terminals AWG24...AWG16 for BUS
Tightening Torque	0.2...0.25 N.m flat Ø 2.5 mm screwdriver 0.5...0.6 N.m flat Ø 3.5 mm screwdriver

Environment

Standards	IEC 62026-1
Ambient Air Temperature For Operation	-25...55 °C
Ip Degree Of Protection	IP20 conforming to IEC 60529

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	5.0 cm
Package 1 Length	11.3 cm
Package 1 Weight	110.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	35
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.16 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins