# **Product datasheet**

Specification





# PM5310 Meter, modbus, up to 31st H, 256K 2DI/2DO 35 alarms

Local distributor code:

398144380 METSEPM5310

EAN Code: 3606480614002

#### Main

Range	PowerLogic
Product Name	PowerLogic PM5000
Device Short Name	PM5310
Product Or Component Type	Power meter

### Complementary

Complementary	
Power Quality Analysis	up to the 31st harmonic
Device Application	Multi-tariff
	Power monitoring
Type Of Measurement	Current
	Voltage
	Frequency
	Power factor
	Energy
	Active and reactive power
Supply Voltage	90450 V AC 4565 Hz
	100300 V DC
Network Frequency	50 Hz
	60 Hz
[In] Rated Current	1A
	5 A
Type Of Network	1P + N
-	3P
	3P + N
Maximum Power Consumption In Va	11 VA at 415 V
Ride-Through Time	80 ms 120 V AC typical
	100 ms 230 V AC typical
	100 ms 415 V AC typical
	50 ms 125 V DC typical
Display Type	Monochrome graphic LCD
Display Resolution	128 x 128 pixels
Sampling Rate	64 samples/cycle
Measurement Current	58500 mA
Analogue Input Type	Voltage (impedance 5 MOhm)
	Current (impedance <= 0.3 mOhm)
Measurement Voltage	35760 V AC 4565 Hz between phases
	20440 V AC 4565 Hz between phase and neutral
Frequency Measurement Range	4565 Hz
Number Of Inputs	2 digital
	·

Measurement Accuracy	Active energy +/- 0.5 %
······································	Reactive energy +/- 2 %
	Active power +/- 0.5 %
	Apparent power +/- 0.5 %
	Frequency +/- 0.05 %
	Power factor +/- 0.5
	Current +/- 0.5 %
	Voltage +/- 0.5 %
	Apparent energy +/- 0.5 %
	Reactive power +/- 2 %
Accuracy Class	Class 0.5S active energy conforming to IEC 62053-22
Number Of Outputs	2 digital
Information Displayed	Tariff (4)
<b>Communication Port Protocol</b>	Modbus RTU and ASCII at 9.6, 19.2 and 38.4 kbauds even/odd or none - 2 wires,
	insulation 2500 V
	JBUS
Communication Port Support	RS485
Data Recording	Eventless
Data Necoraling	Event logs Min/max of instantaneous values
	Alarm logs
	Data logs
	Time stamping
	Maintenance logs
Memory Capacity	256 kB
Connections - Terminals	Voltage circuit: screw terminal block4
	Control circuit: screw terminal block2
	Current transformer: screw terminal block6
	Input/output circuit: screw terminal block6
	Relay output: screw terminal block4
	Ethernet network: RJ45 connector
Mounting Mode	Flush-mounted
Mounting Support	Framework
Standards	EN 50470-3
	IEC 62053-24
	IEC 60529
	EN 50470-1
	UL 61010-1
	IEC 62053-22:2020
	IEC 61557-12:2015
	IEC 62053-23:2020
	IEC 62052-11:2020
	IEC 62052-31:2015
Product Certifications	CE conforming to IEC 61010-1
	CULus conforming to UL 61010-1
Width	96 mm
Depth	72 mm
Height	96 mm
Net Weight	430 g

## **Environment**

Electromagnetic Compatibility	Conducted and radiated emissions class A conforming to EN 55011
	Limits for harmonic current emissions class A conforming to IEC 61000-3-2
	Immunity to conducted disturbances - test level: 150 kHz80 MHz level 3 conforming
	to IEC 61000-4-6
	Voltage dips and interruptions immunity test level 4 conforming to IEC 61000-4-11
	Conducted RF disturbances level 3 conforming to IEC 61000-4-6
	Magnetic field at power frequency level 4 conforming to IEC 61000-4-8
	Conducted and radiated emissions class B conforming to EN 55022
	Limitation of voltage changes, voltage fluctuations and flicker in low-voltage conforming to IEC 61000-3-3
	Electrostatic discharge - test level: 8 kV level 4 conforming to IEC 61000-4-2
	Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3
	Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4
	Surge immunity test level 4 conforming to IEC 61000-4-5
	Voltage dips and interruptions immunity test conforming to IEC 61000-4-11
Ip Degree Of Protection	IP54 display: conforming to IEC 60529
	IP30 rear: conforming to IEC 60529
Relative Humidity	595 % at 50 °C non-condensing
Pollution Degree	2
Ambient Air Temperature For	-2570 °C meter
Operation	-2070 °C display
	-2520 °C (with reduced performance) display
Ambient Air Temperature For Storage	-4085 °C
Operating Altitude	2000 m CAT III
operating militade	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	12.6 cm
Package 1 Length	12.6 cm
Package 1 Weight	492.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.4 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	288
Package 3 Height	105.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	156.0 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information