# **Product datasheet**

Specification





# TeSys Vario - switch disconnector - 40 A - on door

VBD2

Local distributor code: 389855426

EAN Code: 3389110724943

### Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	VBD
Device Application	Preventive maintenance
Product Type	Switch disconnector

## Complementary

Complemental y	
Device Composition	Handle
	Switch
	O.M.O.
Mounting Support	Handle: door
	Switch: door
Mounting Method	Hole with 22.5 mm for handle
Performance Level	High performance
Number Of Poles	3P
Contact Type And Composition	3 NO
[Hallas Batad Onsertional	000 / 40 50/00 //
[Ue] lec Rated Operational Voltage	690 V AC 50/60 Hz
lec Rated Operational Power In W	11 kW at 690 V (AC-3)
lec Rated Operational Fower III W	15 kW at 690 V (AC-3)
	11 kW at 400415 V (AC-3)
	15 kW at 500 V (AC-3)
	18.5 kW at 500 V (AC-23A)
	5.5 kW at 230240 V (AC-3)
	7.5 kW at 230240 V (AC-23A)
	15 kW at 400415 V (AC-23A)
[le] Rated Operational Current	29 A AC-23 Ue: 400 V
[Ith] Conventional Free Air	40 A
Thermal Current	
[Ithe] Conventional Enclosed	32 A
Thermal Current	
Making Capacity ( I Rms)	400 A at 400 V AC-21A
	400 A at 400 V AC-22A
	400 A at 400 V AC-23A
Bus altitus Como altri	
Breaking Capacity	320 A at 400 V (AC-21A)
	320 A at 400 V (AC-22A)
	320 A at 400 V (AC-23A)
Rated Conditional Short Circuit	10 kA at 400 V - associated fuse 50 A aM
Current	10 kA at 400 V - associated fuse 50 A aim
	10 km at 400 v - associated luse 30 m yo
[Icm] Rated Short Circuit Making Capacity	1 kA at 400 V at Ipeak
[Icw] Rated Short Time Withstand Current	480 A at 400 V duration: 1 s

[Uimp] Rated Impulse Withstand	8 kV
Voltage	
Suitability For Isolation	Yes
Network Type	DC
	AC
Intermittent Duty Class	30
Control Type	Rotary handle
Rotary Handle Mounting Style	Direct
Handle Color	Black
Handle Front Plate Color	Black
Rotary Handle Padlocking	1 to 3 padlocks 48 mm
Marking	0 - 1
Mechanical Durability	100000 cycles
Electrical Durability	100000 cycles AC-21
	30000 cycles DC-15
lec Terminal Connection	Power circuit: screw clamp terminals10 mm² - solid
	Power circuit: screw clamp terminals6 mm² - flexible - with cable end
Tightening Torque	Power circuit: 2.1 N.m - on screw clamp terminals
Base Dimension	60 x 60 mm
Height	74 mm
Width	60 mm
Product Weight	0.215 kg

## **Environment**

Standards	IEC 60947-3
Product Certifications	CSA CCC GL UL UKCA
Degree Of Protection	IP20 conforming to IEC 60529 IP65
Protective Treatment	TC
Mechanical Robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
Ambient Air Temperature For Operation	-2050 °C
Fire Resistance	960 °C conforming to IEC 60695-2-1
Compatibility Code	Main switch disconnector

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	8.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	221.0 g

Unit Type Of Package 2	S03
Number Of Units In Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.825 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium\*

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Toxic Heavy Metal Free
<b>②</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>②</b>	Pvc Free
<b>⊘</b>	Halogen Free Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations