Specifications





(!) Discontinued

# pushbutton head for harsh environment - red - with marking

Local distributor code: 398131665

ZB4BC48007

() Discontinued on: 9 Feb 2023

EAN Code: 3606480444623

## Main

| Range Of Product              | Harmony XB4           |
|-------------------------------|-----------------------|
| Product Or Component Type     | Head for push-button  |
| Device Short Name             | ZB4                   |
| Bezel Material                | Chromium plated metal |
| Head Type                     | Standard              |
| Mounting Diameter             | 22.5 mm               |
| Sale Per Indivisible Quantity | 1                     |
| Cap/Operator Or Lens Colour   | Red                   |

# Complementary

| oompicinentai y                   |  |
|-----------------------------------|--|
| Cad Overall Width                 | 37 mm  |
| Cad Overall Height                | 18.5 mm  |
| Cad Overall Depth                 | 37 mm  |
| Net Weight                        | 0.036 kg   |
| Electrical Shock Protection Class | Class I conforming to IEC 61140  |
| Shape Of Signaling Unit Head      | Round  |
| Type Of Operator                  | spring return  |
| Operator Profile                  | Red flush, type H007 (white)   |
| Operator Additional Information   | Vertical mounting  |
| Mechanical Durability             | 10000000 cycles  |
| Vibration Resistance              | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6  |
| Shock Resistance                  | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27  |
| Main Group                        | Harsh environment  |
| Group Of Product                  | Flush marked type H007   |
| Marking                           | Туре Н007  |
| Colour Of Marking                 | White  |
| Electrical Composition Code       | C1 for <9 contacts using single blocks in front mounting<br>C2 for <9 contacts using single and double blocks in front mounting<br>C11 for <3 contacts using single blocks in front mounting |

C15 for <1 contacts using single blocks in front mounting

# Environment

| Ambient Air Temperature For<br>Storage   | -4085 °C  |
|--|---|
| Ambient Air Temperature For<br>Operation | -4070 °C  |
| Ip Degree Of Protection                  | IP66 conforming to IEC 60529<br>IP69K<br>IP67<br>IP69 |
| Nema Degree Of Protection                | NEMA 4 conforming to UL 508<br>NEMA 13<br>NEMA 12     |
| Resistance To High Pressure<br>Washer    | 90 Pa at 82.5 °C                                      |
| Ik Degree Of Protection                  | IK06 conforming to IEC 62262                          |
| Standards                                | IEC 60947-5-1<br>IEC 60947-1<br>UL 508<br>CSA C22.2   |
| Product Certifications                   | CSA<br>CE<br>UL                                       |

# **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 3.76 cm |
| Package 1 Width              | 3.7 cm  |
| Package 1 Length             | 3.7 cm  |
| Package 1 Weight             | 36.0 g  |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

# Well-being performance


Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

## **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration |
| China Rohs Regulation    | China RoHS declaration  |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |

## **Dimensions Drawings**


## Dimensions



Mounting and Clearance


### Installation on Flat Surface

## Without Protective Guard



(1) Ø22.5 mm recommended (Ø22.3  $_0^{+0.4}$ ) / Ø0.89 in. recommended (Ø0.88  $_0^{+0.016}$ )

#### With Protective Guard




(1) Ø22.5 mm recommended (Ø22.3  $_0^{+0.4}$ ) / Ø0.89 in. recommended (Ø0.88  $_0^{+0.016}$ )

**Technical Description** 


Marking Type H007



Electrical Composition Corresponding to Code C1



Electrical Composition Corresponding to Code C2



Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1



Electrical Composition Corresponding to Code C15



1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



### Legend

Single contact



#### Double contact



Light block



#### Possible location

