Specifications



Transformer, dry type, encapsulated, 10kVA, 1 phase, 240x480V primary, 120/240V secondary, 13B, 115C rise

10S1FSS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 6,432.00 USD

Main

Product Or Component Type	Dry Sealed Transformer
Primary To Secondary Voltage	240 x 480 V 120/240 V
Full Capacity Taps	0

Complementary

Enclosure Code13BPhase1 phasePower Rating10 kVATemperature Rise115 °CHeight14.75 in (374.65 mm)Width9.75 in (247.65 mm)Depth11.75 in (298.45 mm)Enclosure MountingWall mountedEnclosure MaterialStainless Steel		J
Power Rating 10 kVA Temperature Rise 115 °C Height 14.75 in (374.65 mm) Width 9.75 in (247.65 mm) Depth 11.75 in (298.45 mm) Enclosure Mounting Wall mounted	Enclosure Code	13B
Temperature Rise 115 °C Height 14.75 in (374.65 mm) Width 9.75 in (247.65 mm) Depth 11.75 in (298.45 mm) Enclosure Mounting Wall mounted	Phase	1 phase
Height 14.75 in (374.65 mm) Width 9.75 in (247.65 mm) Depth 11.75 in (298.45 mm) Enclosure Mounting Wall mounted	Power Rating	10 kVA
Width 9.75 in (247.65 mm) Depth 11.75 in (298.45 mm) Enclosure Mounting Wall mounted	Temperature Rise	115 °C
Depth 11.75 in (298.45 mm) Enclosure Mounting Wall mounted	Height	14.75 in (374.65 mm)
Enclosure Mounting Wall mounted	Width	9.75 in (247.65 mm)
	Depth	11.75 in (298.45 mm)
Enclosure Material Stainless Steel	Enclosure Mounting	Wall mounted
	Enclosure Material	Stainless Steel

Environment

Enclosure Type	NEMA 3R
Insulation Temperature	356 °F (180 °C)
Product Certifications	CSA cULus UL Listed

Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
Gtin	785901555490
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1

PCE

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Number Of Units In Package 1	1
Package 1 Height	11.22 in (28.499 cm)
Package 1 Width	10.24 in (26.01 cm)
Package 1 Length	13.23 in (33.604 cm)
Package 1 Weight	165.00 lb(US) (74.843 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov