



MX shunt trip release, Compact NS 100 to 630, 380 VAC to 415 VAC 50 Hz, 440 VAC to 480 VAC 60 Hz

29388

① Discontinued

Main

Range	ComPact
Range Of Product	NS400630
	NS400630 DC
	NSF150250
	NS125E
	NSJ400600
	NS100250
	NB400600
	NS100250 DC
	NR400630
	NR100250
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Shunt trip release
[Uc] Control Circuit Voltage	380415 V AC 50 Hz
	440480 V AC 60 Hz
Range Compatibility	ComPact ComPact NS
	ComPact Compact NB
	ComPact Compact NR
	ComPact Compact NSF
	ComPact Compact NSJ

Complementary

Operating Threshold	0.71.1 x Un	
Control Signal Type	Impulse Maintained	
Impulse Duration	>= 20 ms	
Auxiliary Connection Terminal	screw terminal 0.000.00 in ² (01.5 mm ²)	

Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES		
Discount Schedule	DE2		
Gtin	00785901109990		
Returnability	No		

Packing Units

Jnit Type Of	Package 1	PCE

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number Of Units In Package 1

Contractual warranty

Warranty

18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Certifications & Standards

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration