





Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, 8 pin, DPDT, 2 NO, 2 NC, 12 VAC coil

8501KPR12V14

Product availability: Stock - Normally stocked in distribution facility

Price\*: 47.58 USD

#### Main

Product Range	8501K
Product Type	Relay
Relay Type	General purpose
Mounting Type	Socket
Contact Composition	DPDT
[Uc] Control Circuit Voltage	24 V AC
Pilot Light	No indicator
Manual Operator	Without test button

### Complementary

Horsepower Rating	1 hp 277 V AC
	0.33 hp 120 V AC
Breaking Capacity	3 A 120 V AC inductive control circuit UL 508
	1.5 A 240 V AC inductive control circuit UL 508
	10 A 277 V AC resistive control circuit UL 508
	10 A 30 V DC resistive control circuit UL 508
Maximum Switching Voltage	300 V AC
	30 V DC
Contact Material	Silver alloy (AgNi)
Operating Time	20 ms - pick-up
	20 ms - drop-out
Shape Of Pins	Tubular
For Use With	8501NR52
	8501NR51

#### **Environment**

Ambient Temperature Range - Operational	-40131 °F (-4055 °C)
Product Certifications	UL Listed UL Recognized CSA CE
Height	2.66 in (67.56 mm)
Width	1.4 in (35.56 mm)
Depth	1.4 in (35.56 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Ordering and shipping details

Category	US10CP221141
Discount Schedule	0CP2
Gtin	785901981107
Returnability	Yes
Country Of Origin	CN

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.70 in (4.318 cm)
Package 1 Width	1.70 in (4.318 cm)
Package 1 Length	3.00 in (7.62 cm)
Package 1 Weight	3.20 oz (90.718 g)
Unit Type Of Package 2	PAL
Number Of Units In Package 2	83
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	17.45 lb(US) (7.913 kg)



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Reach Free Of Svhc



Rohs Exemption Information


Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

**Dimensions Drawings** 

#### **Approximate Dimensions**




## **Product data sheet**

## 8501KPR12V14

Connections and Schema

#### **Connections and Wiring Diagrams**

### 8501KP12 • • •



NEMA IEC