





(!) Discontinued

Plug in relay, Type KU, blade, 0.5 HP at 240 VAC, 10A resistive at 120 VAC, 8 blade, DPDT, 2 NO, 2 NC, 12 VDC coil

8501KUDR12P14V51

- ! Discontinued on: Dec 2, 2020
- ! End-of-service on: Dec 31, 2020

# Main

| Product Range                | 8501K                               |
|------------------------------|-------------------------------------|
| Product Type                 | Relay                               |
| Relay Type                   | General purpose                     |
| Mounting Type                | Socket                              |
| Contact Composition          | DPDT                                |
| [Uc] Control Circuit Voltage | 12 V DC                             |
| Pilot Light                  | Indicator light relay energised LED |

#### Complementary

| Horsepower Rating         | 1 hp 277 V AC<br>0.33 hp 120 V AC  |
|---------------------------|--|
| Breaking Capacity         | 3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 277 V AC resistive control circuit UL 508 10 A 30 V DC resistive control circuit UL 508 |
| Maximum Switching Voltage | 300 V AC<br>30 V DC  |
| Contact Material          | Silver alloy (AgNi)  |
| Operating Time            | 20 ms - pick-up<br>20 ms - drop-out  |
| Shape Of Pins             | Spade  |
| For Use With              | 8501NR82   |

#### **Environment**

| Ambient Temperature Range - Operational | -40131 °F (-4055 °C)           |
|---|--------------------------------|
| Product Certifications                  | UL Listed UL Recognized CSA CE |
| Height                                  | 2.25 in (57.15 mm)             |
| Width                                   | 1.37 in (34.80 mm)             |
| Depth                                   | 1.4 in (35.56 mm)              |

## Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Category          | 21144-8501 KU  |
|-------------------|----------------|
| Discount Schedule | CP2            |
| Gtin              | 00785901984528 |
| Returnability     | No             |
| Country Of Origin | CN             |

# **Packing Units**

| Unit Type Of Package 1 | PCE |
|------------------------|-----|
|                        |     |



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

## **Certifications & Standards**

| Reach Regulation          | REACh Declaration  |
|---------------------------|--|
| Eu Rohs Directive         | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration   |
| China Rohs Regulation     | China RoHS declaration   |
| Environmental Disclosure  | Product Environmental Profile  |
| Circularity Profile       | No need of specific recycling operations   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |