Product data sheet

Specifications



NEMA Control Relay, Type X, timing, 1 minute on delay, 10A resistive at 600 VAC, 0 normally open, 120 VAC 60 Hz coil

8501XO00XTE1V02

(!) Discontinued on: Jul 6, 2022

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	8501X
Relay Type	Timing
Product	Relay
Current Rating	10 A AC 5 A DC
Number Of Poles	0P
Voltage Rating	600 V AC

Complementary

complementary		
Coil Voltage	110 V AC 50 Hz	
	120 V AC 60 Hz	
Coil Voltage Limints	Operational 0.851.1 Uc AC 50/60 Hz	
Breaking Current	6 A 120 V AC inductive control circuit UL 508	
	3 A 240 V AC inductive control circuit UL 508	
	1.5 A 480 V AC inductive control circuit UL 508	
	1.2 A 600 V AC inductive control circuit UL 508	
	10 A <= 600 V AC resistive control circuit UL 508	
	1.1 A 125 V DC inductive control circuit UL 508	
	0.55 A 250 V DC inductive control circuit UL 508	
	0.2 A 301600 V DC inductive control circuit UL 508	
	4 A 125 V DC resistive control circuit UL 508	
	0.8 A 250 V DC resistive control circuit UL 508	
Making Current	60 A 120 V AC inductive control circuit UL 508	
-	30 A 240 V AC inductive control circuit UL 508	
	15 A 480 V AC inductive control circuit UL 508	
	12 A 600 V AC inductive control circuit UL 508	
	10 A <= 600 V AC resistive control circuit UL 508	
	1.1 A 125 V DC inductive control circuit UL 508	
	0.55 A 250 V DC inductive control circuit UL 508	
	0.2 A 301600 V DC inductive control circuit UL 508	
	4 A 125 V DC inductive control circuit UL 508	
	0.8 A 250 V DC resistive control circuit UL 508	
Time Delay Type	On-delay	
Time Delay Time	0.260 s	
Coil Inrush Power	148 VA 60 Hz	
	143 VA 50 Hz	
Coil Sealed Power	23 VA 60 Hz	
	25 VA 50 Hz	
Device Operating Time	15 ms - pick-up	
	16 ms - drop-out	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Contact Configuration	Without
Electrical Connection	Screw clamp terminals
Wire Gauge	AWG 18AWG 12 copper
Terminal Tightening Torque	Control circuit 9.0312.04 lbf.in (1.021.36 N.m) screw terminal
Mounting Type	Panel
Operating Temperature Range	-40160 °F (-4071 °C)
Height	3.5 in (88.90 mm)
Width	2.23 in (56.64 mm)
Depth	6.55 in (166.37 mm)

Environment

Product Certifications

UL listed file E78403 CCN NKCR CSA LR60905 class 3211 03

Ordering and shipping details

Category	US10CP221158
Discount Schedule	0CP2
Gtin	785901537380
Returnability	Νο
Country Of Origin	МХ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.54 in (6.452 cm)
Package 1 Width	1.00 in (2.54 cm)
Package 1 Length	6.45 in (16.387 cm)
Package 1 Weight	2.60 lb(US) (1.179 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov