Product data sheet

Specifications

SQUARE D



Contactor, Type S, combination lighting, electrically held, 30A, 3 pole, 600 V fuse, 440/480 VAC 50/60 Hz coil, NEMA 1

8903SMG61V06

(!) To be discontinued on: Apr 30, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor
Туре	S

Complementary

e emprementar j	
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Current Rating	30 A
Number Of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnector Device Type	Fusible disconnect switch R, 30 A 600 V
Electrical Connection	Lugs
Height	22.52 in (572 mm)
Depth	8.39 in (213 mm)
Width	9.49 in (241 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
Returnability	No
Country Of Origin	MX

Packing Units

Unit Type Of Package 1

PCE

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Number Of Units In Package 1	1
Package 1 Height	22.52 in (57.2 cm)
Package 1 Width	9.49 in (24.1 cm)
Package 1 Length	8.39 in (21.3 cm)
Package 1 Weight	27.84 lb(US) (12.63 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Under investigation

China Rohs Regulation

China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.