





# PUSHBUTTON 600VAC 10AMP 30MM SK +OPTIONS

9001SK1L7GH13

Discontinued on: Jul 12, 2021



#### Main

Range Of Product	Harmony 9001SK	
Product Or Component Type	Illuminated push-button	
Device Short Name	9001SK	
Type Of Operator	spring return	
Operator Profile	Green flush	
Operator Additional Information	Full guard in plastic	
Light Block Supply	Via integral transformer	

## Complementary

Bezel Material	Plastic	
Mounting Diameter	1.18 in (30 mm)	
Light Source	incandescent	
Bulb Base	BA 9s	
[Us] Rated Supply Voltage	220240 V AC	
Contacts Type And Composition	1 C/O	
Connections - Terminals	Screw clamp terminals 1 x 0.222 x 1.5 mm² EN/IEC 60947-1	
Tightening Torque	7.08 lbf.in (0.8 N.m) EN/IEC 60947-1	
Shape Of Screw Head	Cross slotted	
Mechanical Durability	5000000 cycles	
Operating Position	Any position	
[le] Rated Operational Current	0.55 A 125 V, DC-13, A600-Q600 NEMA	
[Ui] Rated Insulation Voltage	250 V 3)EN/IEC 60947-1	
[Uimp] Rated Impulse Withstand Voltage	2.5 kV EN/IEC 60947-1	
Contacts Material	Silver alloy contacts	
Contact Operation	<b>Operation</b> Standard	
Short-Circuit Protection	10 A cartridge fuse EN/IEC 60947-5-1	
[Ith] Conventional Free Air Thermal Current	10 A	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

	1.5 kA 480 V AC-15, 720 VA 3 kA 240 V AC-15, 720 VA 6 kA 120 V AC-15, 720 VA 0.1 kA 240 V DC-13
	0.27 kA 250 V DC-13 0.55 kA 125 V DC-13
Net Weight	0.40 lb(US) (0.181 kg)
Device Presentation	Complete product

## **Environment**

Standards	EN/IEC 60947-1 CSA C22.2 No 14 UL 508 JIS C 852 JIS C 4520 EN/IEC 60947-5-1 EN/IEC 60947-5-4
Product Certifications	NEMA UL 508
Protective Treatment	TC
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Vibration Resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock Resistance	50 gn IEC 60068-2-27
Electrical Shock Protection Class	Class II IEC 61140
Ip Degree Of Protection	IP66 IEC 60529
Nema Degree Of Protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3 NEMA 4 NEMA 4

# Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
Gtin	785901040507
Returnability	No
Country Of Origin	MX

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Weight	6.40 oz (181.437 g)	

# **Contractual warranty**

Warranty

May 4, 2024

18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>②</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

May 4, 2024