

Product data sheet

Specifications

SQUARE D



Power distribution block, Linergy, 3 pole, 1 line, 1 load, 310A Cu, 250A Al, 600V

9080LBA363101

Product availability: Stock - Normally stocked in distribution facility

Price*: 107.00 USD

Main

| | |
|----------------|---------------------------------|
| Range | 9080LB |
| Product | Power Distribution Block |
| Current Rating | 310 A copper 250 A aluminium |

Complementary

| | |
|---------------------------------------|--|
| Voltage Rating | 600 V AC/DC |
| Mounting Type | Surface mount |
| Number Of Poles | 3 |
| Terminals Per Pole | 1 line 1 load |
| Wire Size | Line 1, AWG 6...350 kcmil, copper or aluminium Load 1, AWG 6...350 kcmil, copper or aluminium |
| Electrical Connection | Tin plated aluminium lugs |
| Sccr | 100 kA UL 508 A |
| Ambient Air Temperature For Operation | -40...302 °F (-40...150 °C) |
| Block Material | Phenolic; block |
| Terminal Tightening Torque | Line lug 275 lbf.in (31.07 N.m) AWG 6...350 kcmil copper or aluminium Load lug 275 lbf.in (31.07 N.m) AWG 6...350 kcmil copper or aluminium |
| Wire Stripping Length | Line: 1.06 in (26.92 mm) Load: 1.06 in (26.92 mm) |
| Height | 3.38 in (85.85 mm) |
| Width | 1.94 in (49.28 mm) |
| Depth | 2.61 in (66.29 mm) |
| End Barrier | 9080LB33 |
| Net Weight | 1.50 lb(US) (0.68 kg) |

Environment

| | |
|----------------|--|
| Certifications | UL recognized E60616 CCN XCFR2 CE CSA file 70361 class 6228 01 |
|----------------|--|

Ordering and shipping details

| | |
|----------|--------------|
| Category | US10CP121711 |
|----------|--------------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------|--------------|
| Discount Schedule | 0CP1 |
| Gtin | 785901097464 |
| Returnability | Yes |
| Country Of Origin | US |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.00 in (7.62 cm) |
| Package 1 Width | 4.30 in (10.922 cm) |
| Package 1 Length | 5.20 in (13.208 cm) |
| Package 1 Weight | 24.00 oz (680.389 g) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | | |
|---------------------------|---|---------------------|
| ✓ | Reach Free Of Svhc | |
| ✓ | Toxic Heavy Metal Free | |
| ✓ | Mercury Free | |
| ✓ | Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration | |
| Eu Rohs Directive | Compliant | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) | |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | |