Product data sheet

Specifications





Mounting plate, Linergy HK, 3P, 50A, 4.4mm², 190x54x61mm

AK5PA532

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 363.00 USD

Main

RangeLinergyProduct NameHKProduct Or Component TypeMounting platePoles Description3P[Ith] Conventional Free Air Thermal Current25 AI*T On Activation200000 A².sNumber Of Cables3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²)Width4.17 in (106 mm)Height7.48 in (190 mm)Depth2.48 in (63 mm)		
Product Or Component Type Mounting plate Poles Description 3P [Ith] Conventional Free Air 25 A Thermal Current 25 A I²T On Activation 200000 A².s Number Of Cables 3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²) Width 4.17 in (106 mm) Height 7.48 in (190 mm)	Range	Linergy
Poles Description 3P [Ith] Conventional Free Air 25 A Thermal Current 200000 A².s I*T On Activation 200000 A².s Number Of Cables 3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²) Width 4.17 in (106 mm) Height 7.48 in (190 mm)	Product Name	НК
[Ith] Conventional Free Air 25 A Thermal Current 200000 A².s I²T On Activation 200000 A².s Number Of Cables 3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²) Width 4.17 in (106 mm) Height 7.48 in (190 mm)	Product Or Component Type	Mounting plate
Thermal Current 200000 A².s I²T On Activation 200000 A².s Number Of Cables 3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²) Width 4.17 in (106 mm) Height 7.48 in (190 mm)	Poles Description	3P
Number Of Cables 3 0.01 in² (4 mm²) 221 °F (105 °C) 3 0.01 in² (4 mm²) 3 0.01 in² (4 mm²) Width 4.17 in (106 mm) Height 7.48 in (190 mm)		25 A
Width 4.17 in (106 mm) Height 7.48 in (190 mm)	I ² T On Activation	200000 A².s
Height 7.48 in (190 mm)	Number Of Cables	
	Width	4.17 in (106 mm)
Depth 2.48 in (63 mm)	Height	7.48 in (190 mm)
	Depth	2.48 in (63 mm)

Complementary

[Ui] Rated Insulation Voltage	690 V IEC 60439-1
9 Mm Pitches	12
Net Weight	1.57 lb(US) (0.71 kg)

Environment

Standards	IEC 60439
Product Certifications	UL
	DNV
	CSA
	LROS (Lloyds register of shipping)

Ordering and shipping details

Category	US10I1122623
Discount Schedule	0l11
Gtin	3389110576979
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Package 1 Height 3.62 in (9.200 cm) Package 1 Width 4.53 in (11.500 cm) Package 1 Length 9.33 in (23.700 cm) Package 1 Weight 27.94 oz (792.000 g) Unit Type Of Package 2 S03 Number Of Units In Package 2 9 Package 2 Height 11.81 in (30.000 cm) Package 2 Width 11.81 in (30.000 cm) Package 2 Length 15.75 in (40.000 cm) Package 2 Weight 16.70 lb(US) (7.576 kg)		
Package 1 Length9.33 in (23.700 cm)Package 1 Weight27.94 oz (792.000 g)Unit Type Of Package 2S03Number Of Units In Package 29Package 2 Height11.81 in (30.000 cm)Package 2 Width11.81 in (30.000 cm)Package 2 Length15.75 in (40.000 cm)	Package 1 Height	3.62 in (9.200 cm)
Package 1 Weight27.94 oz (792.000 g)Unit Type Of Package 2S03Number Of Units In Package 29Package 2 Height11.81 in (30.000 cm)Package 2 Width11.81 in (30.000 cm)Package 2 Length15.75 in (40.000 cm)	Package 1 Width	4.53 in (11.500 cm)
Unit Type Of Package 2 S03 Number Of Units In Package 2 9 Package 2 Height 11.81 in (30.000 cm) Package 2 Width 11.81 in (30.000 cm) Package 2 Length 15.75 in (40.000 cm)	Package 1 Length	9.33 in (23.700 cm)
Number Of Units In Package 2 9 Package 2 Height 11.81 in (30.000 cm) Package 2 Width 11.81 in (30.000 cm) Package 2 Length 15.75 in (40.000 cm)	Package 1 Weight	27.94 oz (792.000 g)
Package 2 Height 11.81 in (30.000 cm) Package 2 Width 11.81 in (30.000 cm) Package 2 Length 15.75 in (40.000 cm)	Unit Type Of Package 2	S03
Package 2 Width 11.81 in (30.000 cm) Package 2 Length 15.75 in (40.000 cm)	Number Of Units In Package 2	9
Package 2 Length 15.75 in (40.000 cm)	Package 2 Height	11.81 in (30.000 cm)
	Package 2 Width	11.81 in (30.000 cm)
Package 2 Weight 16.70 lb(US) (7.576 kg)	Package 2 Length	15.75 in (40.000 cm)
	Package 2 Weight	16.70 lb(US) (7.576 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

\checkmark	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov