# Product data sheet

Specifications

Green Premium™

## Rack ATS, 200/208V, 30A, L6-30 in, (16) C13 (2) C19 out

AP4432

Discontinued on: Jun 9, 2023

Discontinued

## Overview

| | |
|---|---|
| **Lead Time** | Usually in Stock |

## Main

| | |
|---|---|
| **Main Input Voltage** | 200 V<br>208 V |
| **Main Output Voltage** | 200 V<br>208 V |
| **Input Connection Type** | NEMA L6-30P |
| **Number Of Rack Unit** | 2U |
| **Cable Length** | 8 ft (2.44 m) |
| **Number Of Cables** | 2 |
| **Provided Equipment** | Mounting Hardware<br>Rack Mounting brackets<br>RS-232 configuration cable |

## Physical

| | |
|---|---|
| **Height** | 3.46 in (8.8 cm) |
| **Width** | 17.01 in (43.2 cm) |
| **Depth** | 9.29 in (23.6 cm) |
| **Net Weight** | 14.51 lb(US) (6.58 kg) |
| **Mounting Location** | Front<br>Rear |
| **Mounting Preference** | No preference |
| **Mounting Mode** | Rack-mounted |

## Input

| | |
|---|---|
| **Input Frequency** | 50/60 Hz |
| **Line Rated Current** | 24 A |
| **Max Line Current** | 30 A |
| **Input Current Limits** | 30 A |
| **Load Capacity** | 4992 VA |

## Output

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Maximum Total Current Draw Per Phase** | 30 A |
| **Number Of Power Socket Outlets** | 16 IEC 60320 C13<br>2 IEC 60320 C19 |
| **Protection Type** | Circuit breaker |

## Conformance

| | |
|---|---|
| **Product Certifications** | PSE<br>TÜV-C<br>TÜV-NURTL |
| **Standards** | EN 55022 Class A<br>FCC Part 15 class A |

## Environmental

| | |
|---|---|
| **Ambient Air Temperature For Operation** | 23…113 °F (-5…45 °C) |
| **Relative Humidity** | 5…95 % |
| **Operating Altitude** | 0...10000 ft |
| **Ambient Air Temperature For Storage** | -13…149 °F (-25…65 °C) |
| **Storage Relative Humidity** | 5…95 % |
| **Storage Altitude** | 0…50000 ft (0.00…15240.00 m) |

## Ordering and shipping details

| | |
|---|---|
| **Gtin** | 731304333463 |

## Packing Units

| | |
|---|---|
| **Unit Type Of Package 1** | PCE |
| **Number Of Units In Package 1** | 1 |
| **Package 1 Height** | 8.27 in (21 cm) |
| **Package 1 Width** | 14.02 in (35.6 cm) |
| **Package 1 Length** | 22.99 in (58.4 cm) |
| **Package 1 Weight** | 20.00 lb(US) (9.07 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 2 years repair or replace |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Take-back Transparency RoHS/REACh

## Resource performance

- Take-Back Program Available

## Well-being performance

- Lead Free
- Mercury Free
- Rohs Exemption Information Yes

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant with Exemptions |
| **Environmental Disclosure** | Product Environmental Profile |
| **Circularity Profile** | End of Life Information |