Product data sheet

Specifications





() Discontinued

servo motor BCH, Lexium 28, 60mm, 200W, 0.16kg.cmÂ², without oil seal, smooth, leads connection

BCH2LD0230CA5C

() Discontinued on: Oct 9, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	Lexium 28
Product Or Component Type	Servo motor
Device Short Name	BCH2

Complementary

Complementary		
Maximum Mechanical Speed	5000 rpm	
[Us] Rated Supply Voltage	220 V 110 V	
Phase	Single phase Three phase	
Continuous Stall Current	1.11 A	
Continuous Stall Torque	5.66 lbf.in (0.64 N.m) LXM28 1.5 A, 220 V, single phase 5.66 lbf.in (0.64 N.m) LXM28 1.5 A, 220 V, three phase 5.66 lbf.in (0.64 N.m) LXM28 3.6 A, 110 V, single phase	
Continuous Power	200 W	
Peak Stall Torque	16.99 lbf.in (1.92 N.m) LXM28 1.5 A, 220 V, single phase 16.99 lbf.in (1.92 N.m) LXM28 1.5 A, 220 V, three phase 16.99 lbf.in (1.92 N.m) LXM28 3.6 A, 110 V, single phase	
Nominal Output Power	200 W LXM28 1.5 A, 220 V, single phase 200 W LXM28 1.5 A, 220 V, three phase 200 W LXM28 3.6 A, 110 V, single phase	
Nominal Torque	5.66 lbf.in (0.64 N.m) LXM28 1.5 A, 220 V, single phase 5.66 lbf.in (0.64 N.m) LXM28 1.5 A, 220 V, three phase 5.66 lbf.in (0.64 N.m) LXM28 3.6 A, 110 V, single phase	
Nominal Speed	3000 rpm LXM28 1.5 A, 220 V, single phase 3000 rpm LXM28 1.5 A, 220 V, three phase 3000 rpm LXM28 3.6 A, 110 V, single phase	
Maximum Current Irms	4.31 A LXM28 0.2 kW, 220 V 4.31 A LXM28 0.2 kW, 110 V	
Maximum Permanent Current	1.3 A	
Product Compatibility	LXM28 servo drive 0.2 kW, 220 V, single phase LXM28 servo drive 0.2 kW, 220 V, three phase LXM28 servo drive 0.2 kW, 110 V, single phase	
Shaft End	Smooth shaft	
Shaft Diameter	0.55 in (14 mm)	
Shaft Length	1.18 in (30 mm)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Feedback Type	20 bits single turn absolute encoder
Holding Brake	Without
Mounting Support	Asian standard flange
Motor Flange Size	2.36 in (60 mm)
Electrical Connection	Free lead
Torque Constant	0.58 N.m/A 68 °F (20 °C)
Back Emf Constant	35 V/krpm 68 °F (20 °C)
Rotor Inertia	0.16 kg.cm ²
Stator Resistance	12.2 Ohm 68 °F (20 °C)
Stator Inductance	22.5 mH 68 °F (20 °C)
Stator Electrical Time Constant	1.84 ms 68 °F (20 °C)
Maximum Radial Force Fr	200 N 3000 rpm
Maximum Axial Force Fa	70 N
Brake Pull-In Power	11.2 W
Type Of Cooling	Natural convection
Length	4.09 in (104 mm)
Number Of Motor Stacks	1
Centring Collar Diameter	1.97 in (50 mm)
Centring Collar Depth	0.22 in (5.5 mm)
Number Of Mounting Holes	4
Mounting Holes Diameter	0.22 in (5.5 mm)
Circle Diameter Of The Mounting Holes	2.76 in (70 mm)
Distance Shaft Shoulder-Flange	0.22 in (5.5 mm)
Net Weight	2.25 lb(US) (1.02 kg)

Environment

Ip Degree Of Protection	IP54 IM B5, IM V1 IP50 IM V3
Ambient Air Temperature For Operation	-4104 °F (-2040 °C)

Ordering and shipping details

Category	US1PC5318281
Discount Schedule	PC53
Gtin	3606480733482
Returnability	No
Country Of Origin	CN

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.37 in (11.1 cm)
Package 1 Width	5.71 in (14.5 cm)

Package 1 Length

10.43 in (26.5 cm)

Package 1 Weight

3.68 lb(US) (1.67 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards


REACh Declaration	
Pro-active compliance (Product out of EU RoHS legal scope)	
China RoHS declaration	
Product Environmental Profile	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
End of Life Information	
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Product data sheet

Dimensions Drawings

Dimensions


Dimensions of Motor



	mm	in.
L (without holding brake)	104	4.09
L (with holding brake)	140	5.51
Z	57	2.24

Performance Curves

Torque/Speed Curves with 230 V Single/Three Phase Supply Voltage



Servo Motor with LXM28AU02••• Servo Drive

- 1: Peak torque
- 2: Continuous torque