Product data sheet

Specifications





Circuit breaker, PowerPacT B, 35A, 1 pole, 480Y/277VAC, 18kA, I-Line, thermal magnetic, 80%, A

BDA140351

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 309.00 USD

Main

Range	PowerPact
Product Name	PowerPact B
Device Short Name	BD 035
Product Or Component Type	Circuit breaker
Device Application	Distribution

Complementary

Complementary	
Line Rated Current	35 A
Number Of Poles	1P
Control Type	Toggle
Breaking Capacity Code	D
Breaking Capacity	25 kA 208Y/120 V AC 50/60 Hz UL 489 25 kA 240 V AC 50/60 Hz UL 489 18 kA 480Y/277 V AC 50/60 Hz UL 489 10 kA 125 V DC 50/60 Hz UL 489 14 kA 600/347 V AC 50/60 Hz UL 489
[Ue] Rated Operational Voltage	240 V AC 50/60 Hz UL 489
Network Frequency	50/60 Hz
[Ics] Rated Service Breaking Capacity	25 kA 220240 V AC 50/60 Hz IEC 60947-2
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947-2
Trip Unit Technology	Thermal-magnetic
Continuous Current Rating	80 %
[Ui] Rated Insulation Voltage	800 V IEC 60947-2
Suitability For Isolation	Yes IEC 60947-2
Utilisation Category	Category A
Mechanical Durability	20000 cycles IEC 947-1 Annex K ed 5.2
Electrical Durability	10000 cycles IEC 947-1 Annex K ed 5.2 440 V In
Connection Pitch	1.06 in (27 mm)
Awg Gauge	AWG 14AWG 2/0 aluminium/copper
Local Signalling	Presence of auxiliary contacts flag green)
Mounting Mode	I-Line

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Connection	I-Line connection, line Lugs, load
Mounting Height	1.50 in (38.1 mm)
Tightening Torque	31.8638.94 lbf.in (3.64.4 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 10) 44.2554.87 lbf.in (56.2 N.m) 0.020.11 in² (1070 mm²) (AWG 8AWG 2/0)
Power Wire Stripping Length	0.79 in (20 mm)
Color	Gray RAL 7016)
9 Mm Pitches	3
Height	5.39 in (137 mm)
Width	1.06 in (27 mm)
Depth	3.50 in (89 mm)
Net Weight	1.41 lb(US) (0.6375 kg)
Quantity Per Set	Set of 1
Phase Connection	A
Circuit Breaker Application	HACR rated

Environment

Quality Labels	CE
Standards	EN/IEC 60947-5-1
	NMX J-266
	CSA C22.2 No 5
	UL 489
	EN/IEC 60947-2
	GB 14048.2
	NEMA AB1
Product Certifications	UL
	IEC
	CCC
	EAC
	CSA
	NOM
Ip Degree Of Protection	Front cover IP40 IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Pollution Degree	3 IEC 60947-1
Ambient Air Temperature For Operation	-13158 °F (-2570 °C)
Ambient Air Temperature For Storage	-58185 °F (-5085 °C)
Operating Altitude	< 6561.68 ft (2000 m) without derating
	5000 m with derating

Ordering and shipping details

Category	US10DE201133
Discount Schedule	0DE2
Gtin	785901058885
Returnability	Yes

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	5.39 in (13.7 cm)
Package 1 Width	1.06 in (2.7 cm)
Package 1 Length	3.50 in (8.9 cm)
Package 1 Weight	25.76 oz (730.284 g)

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Pvc Free	
Halogen Free Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov