Product data sheet





servo motor BMH, Lexium 32, 62.5Nm, 3800rpm, keyed shaft, with brake, IP54, 16bit encoder

BMH2052P16F2A

! Discontinued on: Oct 9, 2023



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Device Short Name | ВМН |
|---------------------------|--|
| Product Or Component Type | Servo motor |
| Maximum Mechanical Speed | 3800 rpm |
| Continuous Stall Torque | 553.17 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 400 V, three phase 553.17 lbf.in (62.5 N.m) LXM32.D72N4 24 A, 480 V, three phase |
| Peak Stall Torque | 1504.62 lbf.in (170 N.m) LXM32.D72N4 24 A, 400 V, three phase 1504.62 lbf.in (170 N.m) LXM32.D72N4 24 A, 480 V, three phase |
| Nominal Output Power | 6500 W LXM32.D72N4 24 A, 400 V, three phase 6500 W LXM32.D72N4 24 A, 480 V, three phase |
| Nominal Torque | 368.19 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 400 V, three phase 368.19 lbf.in (41.6 N.m) LXM32.D72N4 24 A, 480 V, three phase |
| Nominal Speed | 1500 rpm LXM32.D72N4 24 A, 400 V, three phase 1500 rpm LXM32.D72N4 24 A, 480 V, three phase |
| Product Compatibility | LXM32.D72N4 400480 V three phase |
| Shaft End | Keyed |
| Ip Degree Of Protection | IP54 standard |
| Speed Feedback Resolution | 32768 points/turn |
| Holding Brake | With |
| Mounting Support | International standard flange |
| Electrical Connection | Rotatable right-angled connectors |

Complementary

| Range Compatibility | Lexium 32 |
|---------------------------|--------------------------|
| [Us] Rated Supply Voltage | 480 V |
| Phase | Three phase |
| Continuous Stall Current | 24.2 A |
| Continuous Power | 7.85 W |
| Maximum Current Irms | 72 A LXM32.D72N4 |
| Maximum Permanent Current | 96.8 A |
| Second Shaft | Without second shaft end |
| Shaft Diameter | 1.50 in (38 mm) |
| Shaft Length | 3.15 in (80 mm) |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Key Width | 2.76 in (70 mm) |
|---|--|
| Feedback Type | Single turn SinCos Hiperface |
| Holding Torque | 708.06 lbf.in (80 N.m) holding brake |
| Motor Flange Size | 8.07 in (205 mm) |
| Number Of Motor Stacks | 2 |
| Torque Constant | 2.6 N.m/A 248 °F (120 °C) |
| Back Emf Constant | 161 V/krpm 248 °F (120 °C) |
| Number Of Motor Poles | 10 |
| Rotor Inertia | 145 kg.cm² |
| Stator Resistance | 0.3 Ohm 68 °F (20 °C) |
| Stator Inductance | 5.6 mH 68 °F (20 °C) |
| Stator Electrical Time Constant | 18.7 ms 68 °F (20 °C) |
| | |
| Maximum Radial Force Fr | 4200 N 1000 rpm 3330 N 2000 rpm 2910 N 3000 rpm |
| Maximum Radial Force Fr Maximum Axial Force Fa | 3330 N 2000 rpm |
| | 3330 N 2000 rpm 2910 N 3000 rpm |
| Maximum Axial Force Fa | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr |
| Maximum Axial Force Fa Brake Pull-In Power | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W |
| Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection |
| Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling Length | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm) |
| Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling Length Centring Collar Diameter | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm) 7.09 in (180 mm) |
| Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling Length Centring Collar Diameter Centring Collar Depth | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm) 7.09 in (180 mm) 0.16 in (4 mm) |
| Maximum Axial Force Fa Brake Pull-In Power Type Of Cooling Length Centring Collar Diameter Centring Collar Depth Number Of Mounting Holes | 3330 N 2000 rpm 2910 N 3000 rpm 0.2 x Fr 40 W Natural convection 17.89 in (454.5 mm) 7.09 in (180 mm) 0.16 in (4 mm) |

Ordering and shipping details

| Category | US1PC5318282 |
|-------------------|---------------|
| Discount Schedule | PC53 |
| Gtin | 3606485203331 |
| Returnability | No |
| Country Of Origin | DE |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 14.17 in (36.0 cm) |
| Package 1 Width | 12.20 in (31.0 cm) |
| Package 1 Length | 28.74 in (73.0 cm) |
| Package 1 Weight | 127.87 lb(US) (58.0 kg) |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Mercury Free | |
|----------|----------------------------|-----|
| | Rohs Exemption Information | Yes |
| ② | Pvc Free | |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | No need of specific recycling operations |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |