Product data sheet

Specifications





(!) Discontinued

TeSys F magnetic latching contactor - 3P(3 NO) - 150 A - 110 V DC coil

CR1F150FZ7

Discontinued on: Jul 12, 2021

Main

Main		
Range	TeSys	
Product Name	TeSys F	
Product Or Component Type	Magnetic latching contactor	
Device Short Name	CR1F	
Device Application	Control	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-1 AC-4 AC-3	
Poles Description	3P	
Power Pole Contact Composition	3 NO	
[Ue] Rated Operational Voltage	1000 V AC 25200 Hz	
[le] Rated Operational Current	150 A (at <104 °F (40 °C)) at <= 440 V AC AC-3 250 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 138 A (at <104 °F (40 °C)) at <= 440 V AC AC-4	
Motor Power Kw	75 kW at 400 V AC 50/60 Hz (AC-4)	
Control Circuit Type	DC low consumption	
[Uc] Control Circuit Voltage	110 V DC	
Irms Rated Making Capacity	1700 A	
Rated Breaking Capacity	1500 A at 220440 V 1200 A at 500 V 450 A at 1000 V 1100 A at 660/690 V	
[Icw] Rated Short-Time Withstand Current	1200 A 104 °F (40 °C) - 1 s 1200 A 104 °F (40 °C) - 5 s 1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min	
Associated Fuse Rating	160 A aM at <= 440 V 250 A BS88 at <= 440 V 250 A gG at <= 440 V	
Average Impedance	0.45 mOhm - Ith 250 A 50 Hz	
[Ui] Rated Insulation Voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Power Dissipation Per Pole	6 W AC-3 18 W AC-1	
Connections - Terminals	lugs-ring terminals 1 0.19 in² (120 mm²) connector 1 0.19 in² (120 mm²) bars 2 25 x 3 mm Power circuit bolted connection	
Tightening Torque	159.31 lbf.in (18 N.m)	
Operating Time	3540 ms latching 50100 ms unlatching	
Mechanical Durability	1 Mcycles	
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)	

Complementary

Control Circuit Voltage Limits	Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc
Average Consumption	500 W DC latching 15 W DC unlatching

Environment

Protective Treatment	TC	
Ambient Air Temperature For Operation	5158 °F (-1570 °C)	
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)	
Operating Altitude	9842.52 ft (3000 m) without derating	
Height	6.69 in (170 mm)	
Width	6.44 in (163.5 mm)	
Depth	6.73 in (171 mm)	
Net Weight	7.72 lb(US) (3.5 kg)	

Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV	
Discount Schedule	112	
Gtin	3389110547887	
Returnability	No	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	7.87 in (20 cm)	
Package 1 Width	8.07 in (20.5 cm)	
Package 1 Length	9.06 in (23 cm)	
Package 1 Weight	8.19 lb(US) (3.715 kg)	

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov