Product data sheet

Specification





TeSys F magnetic latching contactor - 4P(4 NO) - 400 A - 110 V AC/DC coil

CR1F4004F7

! Discontinued on: Jan 23, 2021

(!) Discontinued

Main

Range	TeSys
Product Name	TeSys F
Product Or Component Type	Magnetic latching contactor
Device Short Name	CR1F
Device Application	Control
Contactor Application	Motor control Resistive load
Utilisation Category	AC-4 AC-1 AC-3
Poles Description	4P
Power Pole Contact Composition	4 NO
[Ue] Rated Operational Voltage	1000 V AC 25200 Hz
[le] Rated Operational Current	400 A (at <104 °F (40 °C)) at <= 440 V AC AC-3 500 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 370 A (at <104 °F (40 °C)) at <= 440 V AC AC-4
Control Circuit Type	AC 50400 Hz DC standard
[Uc] Control Circuit Voltage	110 V AC 50400 Hz 110 V DC
Irms Rated Making Capacity	4500 A
Rated Breaking Capacity	4000 A at 220440 V 3500 A at 500 V 1200 A at 1000 V 3000 A at 660/690 V
[Icw] Rated Short-Time Withstand Current	3600 A 104 °F (40 °C) - 1 s 3600 A 104 °F (40 °C) - 5 s 3600 A 104 °F (40 °C) - 10 s 2400 A 104 °F (40 °C) - 30 s 1700 A 104 °F (40 °C) - 1 min 1200 A 104 °F (40 °C) - 3 min 1000 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	400 A aM at <= 440 V 500 A BS88 at <= 440 V 500 A gG at <= 440 V
Average Impedance	0.28 mOhm - Ith 500 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Power Dissipation Per Pole	45 W AC-3 70 W AC-1
Connections - Terminals	lugs-ring terminals 2 0.23 in² (150 mm²) bars 2 30 x 5 mm Power circuit bolted connection
Tightening Torque	309.78 lbf.in (35 N.m)
Operating Time	4075 ms latching 50100 ms unlatching
Mechanical Durability	1 Mcycles
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)

Complementary

Control Circuit Voltage Limits	Latching: 0.851.1 Uc Unlatching: 0.851.1 Uc
Average Consumption	1600 VA AC 50400 Hz latching 16 VA AC 50400 Hz unlatching 1600 VA DC latching 16 VA DC unlatching

Environment

Protective Treatment	TC
Ambient Air Temperature For Operation	5158 °F (-1570 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Operating Altitude	9842.52 ft (3000 m) without derating
Height	8.11 in (206 mm)
Width	10.28 in (261 mm)
Depth	8.62 in (219 mm)
Net Weight	22.49 lb(US) (10.2 kg)

Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	112
Gtin	03389110548617
Returnability	No
Country Of Origin	CZ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty	18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov