



Mini circuit breaker, E-Frame, 15A, 1 pole, 277 VAC, 25 kA max, bolt on, 50 degrees C

EDB14015CA

! Discontinued on: Jan 11, 2023

① Discontinued

Main

| Range Of Product | 125 A Frame EDB-EGB-EJB | |
|---------------------------|---------------------------|--|
| Product Or Component Type | Miniature circuit-breaker | |
| Device Short Name | EDB | |
| Module Type | E-Frame | |
| Trip Unit Rating | 875 A | |

Complementary

| · · · · · · · · · · · · · · · · · · | |
|-------------------------------------|---|
| Line Rated Current | 15 A |
| Maximum Operating Voltage | 277 V AC |
| Awg Gauge | AWG 12AWG 6 aluminium |
| | AWG 14AWG 6 copper |
| Breaking Capacity | 18 kA 277 V AC |
| | 18 kA 240 V AC |
| | 25 kA 120 V AC |
| | 18 kA 120/240 V AC |
| Circuit Breaker Application | Switching Duty rated |
| | HACR rated |
| | HID rated |
| Electrical Connection | Lugs aluminium |
| Holding Current | 270 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 1 |
| Number Of Spaces | 1 |
| Number Of Spaces Required | 1 |
| Product Destination | NF panelboard |
| Protection Type | Short-circuit |
| | Overload |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | D |
| Tightening Torque | 30.09 lbf.in (3.4 N.m) 0.000.02 in² (2.516 mm²) (AWG 14AWG 6) |
| Height | 5.66 in (143.76 mm) |
| Width | 0.98 in (24.89 mm) |
| Depth | 4.05 in (102.87 mm) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

 Net Weight
 2 lb(US) (0.91 kg)

Environment

| Product Certifications | cULus |
|--|----------------|
| Ambient Air Temperature For Operation | 122 °F (50 °C) |

Ordering and shipping details

| Category | 00931-EDB CIRCUIT BREAKERS |
|-------------------|----------------------------|
| Discount Schedule | DE2 |
| Gtin | 3606486143247 |
| Returnability | No |
| Country Of Origin | MX |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.80 in (4.572 cm) |
| Package 1 Width | 6.10 in (15.494 cm) |
| Package 1 Length | 10.20 in (25.908 cm) |
| Package 1 Weight | 21.16 oz (599.967 g) |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|----------------------------|--|
| Rohs Exemption Information | Yes |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |