Product data sheet

Specifications

Green Premium		Circuit breaker, FA, 240V, 90A, 2 pole
		Discontinued on: Oct 28, 2021
	① Discontinued	Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Or Component Type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

Complementary

Line Rated Current90 ANumber Of Poles2PBreaking Capacity CodeAMounting ModeUnit mountMagnetic Hold Current900 AMagnetic Tripping Current1700 AElectrical ConnectionLugs, load Lugs, lineTerminal IdentifierAL100FAPhase ConnectionABCHeight6.4 in (162.56 mm)Width3 in (76.20 mm)Depth4.13 in (104.90 mm)	· · · · · · · · · · · · · · · · · · ·	
Breaking Capacity Code A Mounting Mode Unit mount Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Terminal Identifier AL100FA ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Line Rated Current	90 A
Mounting ModeUnit mountMagnetic Hold Current900 AMagnetic Tripping Current1700 AElectrical ConnectionLugs, load Lugs, lineTerminal IdentifierAL100FAPhase ConnectionABCHeight6.4 in (162.56 mm)Width3 in (76.20 mm)Depth4.13 in (104.90 mm)	Number Of Poles	2P
Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line 1700 FA Terminal Identifier AL100FA Phase Connection ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Breaking Capacity Code	A
Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Lugs, line Terminal Identifier AL100FA Phase Connection ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Mounting Mode	Unit mount
Electrical Connection Lugs, load Lugs, line Lugs, line Terminal Identifier AL100FA Phase Connection ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Magnetic Hold Current	900 A
Lugs, line Terminal Identifier AL100FA Phase Connection ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Magnetic Tripping Current	1700 A
Phase Connection ABC Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Electrical Connection	
Height 6.4 in (162.56 mm) Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Terminal Identifier	AL100FA
Width 3 in (76.20 mm) Depth 4.13 in (104.90 mm)	Phase Connection	ABC
Depth 4.13 in (104.90 mm)	Height	6.4 in (162.56 mm)
	Width	3 in (76.20 mm)
	Depth	4.13 in (104.90 mm)
Circuit Breaker Application HACR rated	Circuit Breaker Application	HACR rated

Environment

Certifications	UL Listed CSA

Ordering and shipping details

Category	US10DE200901
Discount Schedule	0DE2
Gtin	785901891215
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1

PCE

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Number Of Units In Package 1	1
Package 1 Height	4.50 in (11.43 cm)
Package 1 Width	6.20 in (15.748 cm)
Package 1 Length	9.80 in (24.892 cm)
Package 1 Weight	3.36 lb(US) (1.525 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile