





① Discontinued

Circuit breaker, FH, 600V, 100A

FHL36100G

Main

| Product Or Component Type | Circuit breaker |
|---------------------------|------------------|
| Trip Unit Technology | Thermal-magnetic |

Complementary

| Line Rated Current 100 A Number Of Poles 3P Breaking Capacity Code H Mounting Mode Unit mount Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Terminal Identifier AL 100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 1/0) 48.C Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) Depth 4.13 in (104.90 mm) | · · · · · · · · · · · · · · · · · · | |
|--|-------------------------------------|---|
| Breaking Capacity Code | ine Rated Current | 100 A |
| Mounting Mode Unit mount Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Terminal Identifier AL100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Number Of Poles | 3P |
| Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Terminal Identifier AL100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Breaking Capacity Code | н |
| Magnetic Tripping Current 1700 A Electrical Connection Lugs, load Lugs, line Terminal Identifier AL100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Mounting Mode | Unit mount |
| Electrical Connection Lugs, load Lugs, line Terminal Identifier AL100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 1/0) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Magnetic Hold Current | 900 A |
| Lugs, line Terminal Identifier AL100FA Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Magnetic Tripping Current | 1700 A |
| Tightening Torque 79.66 lbf.in (9 N.m) 0.000.08 in² (2.0853.48 mm²) (AWG 14AWG 1/0) 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Electrical Connection | • . |
| 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) 44.25 lbf.in (5 N.m) 0.010.01 in² (3.315.26 mm²) (AWG 12AWG 10) Phase Connection ABC Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Terminal Identifier | AL100FA |
| Height 6.4 in (162.56 mm) Width 4.5 in (114.30 mm) | Fightening Torque | 79.66 lbf.in (9 N.m) 0.010.08 in² (3.3153.48 mm²) (AWG 12AWG 1/0) |
| Width 4.5 in (114.30 mm) | Phase Connection | ABC |
| | Height | 6.4 in (162.56 mm) |
| Depth 4.13 in (104.90 mm) | Width | 4.5 in (114.30 mm) |
| | Depth | 4.13 in (104.90 mm) |
| Circuit Breaker Application HACR rated | Circuit Breaker Application | HACR rated |

Environment

| Certifications | CSA | |
|----------------|-----------|--|
| | UL Listed | |

Ordering and shipping details

| Category | 00903-FAL/FHL 600V | |
|-------------------|--------------------|--|
| Discount Schedule | DE2 | |
| Gtin | 00785901617822 | |
| Returnability | No | |
| Country Of Origin | MX | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
|---------------------------|---|
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.For more information go to www.p65warnings.ca.gov |