

Product data sheet

Specifications



auxiliary early-break contact - TeSys GS - 2 OC - 630...1250 A

GS1AM4

! Discontinued

Main

Range Of Product	TeSys GS 630...1250
Device Short Name	auxiliary early break and signalling contact
Product Or Component Type	Auxiliary contact
Product Compatibility	GS 630...1250
Contacts Type And Composition	4 C/O
[Ie] Rated Operational Current	12 A 24 V DC-13 2 A 440 V AC-15 2 A 48 V DC-13 3 A 400/415 V AC-15 4 A 230 V AC-15 5 A 127 V AC-15 0.4 A 220 V DC-13 0.6 A 110 V DC-13

Complementary

Fuse Type	DIN NFC BS
Net Weight	0.11 lb(US) (0.05 kg)

Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
Gtin	3389110563245
Returnability	No
Country Of Origin	FR

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
