Product data sheet

Specifications





Galaxy VS UPS 30kW 208V for External Batteries, Start-up 5x8

GVSUPS30KFS

Overview

Presentation

Highly efficient, easy-to-deploy 30kW, 208V 3-phase uninterruptible power supply (UPS) that brings best-in-class power protection to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Compact design, high-density technology and modular architecture keep total cost of ownership low and operational efficiency at the highest levels. Galaxy VS reduces your energy losses by up to 66% with the patented ECOnversion mode – reaching up to 99% efficiency levels and delivering more energy savings than even our industry-leading 97% efficiency in normal operating mode. The UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management via your smartphone. Includes 5x8 start-up service. For battery runtime details, see the runtime charts published under the Documents tab.

Lead Time

Usually Ships within 2 Weeks

Main

Mann					
Main Input Voltage	208 V 3 phase				
Other Input Voltage	200 V 220 V				
Main Output Voltage	208 V 3 phase				
Other Output Voltage	200 V 220 V				
Kw Rating	30 kW				
Rated Power In Va	30 kVA				
Output Connector Type	Hard Wire 5-wire (3PH + N + G) 1				
Battery Type	External battery system Li-Ion (Lithium Ion) VRLA				
Provided Equipment	Dust filter Installation guide Integrated network management Power modules ship installed Start-Up Service Top and bottom cable entry				

Batteries & Runtime

Efficiency	View Efficiency Graph □	
Included Battery Modules	0	
Battery Slots Empty	0	
Battery Voltage	384-480VDC	
End Of Discharge Battery Voltage	307 V DC	
End Of Discharge Maximum Battery Current	102 A	
Battery Power In Vah	0 VAh runtime	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Extendable Run Time 0

General

Bypass Voltage Tolerance	+/- 10 %
Max Bypass Input Current	105 A
Redundant	No

Physical

Color	White
Height	58.46 in (148.5 cm)
Width	20.51 in (52.1 cm)
Depth	33.35 in (84.7 cm)
Net Weight	524.70 lb(US) (238 kg)
Usb Compatible	No

Input

Input Frequency	40 - 70 Hz	
Number Of Input Connectors	1 Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G)	
Efficiency At Full Load	177239 V 208 V	
Maximum Input Current Per Phase	110 A	
Maximum Short Circuit Withstand (Icw)	65 kA	
Input Total Harmonic Distortion	Less than 3% for full load	
Load Power Factor	From 0.7 leading to 0.7 lagging without any derating	
Input Power Factor At Full Load	0.00	

Input Power Factor At Full Load 0.99

Output

Max Configurable Power (Watts)	30 kW	
Harmonic Distortion	Less than 3%	
Output Frequency (Sync To Mains)	50 Hz sync to mains 60 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced	
Crest Factor	2.5	
Wave Type	Sine wave	
Output Voltage Tolerance	+/-1% after 50ms	
Output Voltage Thd	< 1% linear load and < 3% non-linear load	
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%	
Bypass Type	Built-in Static Bypass	
Maximum Configurable Power In Va	30 KVA	

Conformance

;	SA	۱ (Cź	22	.2	2 1	١o	1	10	7.	3		
(СС		Pa	art	: 1	5	c	a	ss	; A	٩		
	С	6	2()4	0	-3							
	С	6	07	72	1	-4	-2	L	.e	ve	el	21	M2
ļ	Ŀ	17	7	8	5t	h	e	di	tic	n			
		6 6	Pa 20	art 04 72	: 1 .0. !1.	5 -3 -4	cl -2	a L	ss .e	s A	٩	21	M2

Environmental

Ambient Air Temperature For Operation	32104 °F (040 °C)		
Relative Humidity	095 % non-condensing		
Operating Altitude	03281 ft		
Ambient Air Temperature For Storage	-13131 °F (-2555 °C)		
Storage Relative Humidity	1080 % non-condensing		
Storage Altitude	050000 ft (0.0015240.00 m)		
Acoustic Level	65 dBA		
Heat Dissipation	5487 Btu/h		
Ip Degree Of Protection	IP21		

Communications & Management

Free Slots	1
Control Panel	Touch Screen LCD User Interface

Ordering and shipping details

Gtin

731304641797

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	66.14 in (168 cm)
Package 1 Width	38.98 in (99 cm)
Package 1 Length	25.20 in (64 cm)
Package 1 Weight	606.27 lb(US) (275 kg)

Contractual warranty

Warranty

1 year on-site repair or replace with factory authorized Start-Up

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information