Product data sheet

Specification





Cam switch body, Harmony K, Ø 22mm, plastic, 3 pole, with 0 position, 90°, 20A

K2C003H

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 177.00 USD

Main

| Range Of Product | Harmony K | |
|--|-------------------------------|--|
| Product Or Component Type | Cam switch body | |
| Component Name | K2 | |
| [Ith] Conventional Free Air Thermal Current | 20 A | |
| Sub-Assembly Composition | Contact blocks + fixing plate | |
| Cam Switch Function | Switch | |
| Off Position | With Off position | |
| Poles Description | 3P | |
| Switching Positions | Right: 0° - 90° | |
| Mounting Location | Front | |
| Fixing Mode | Ø 22 mm hole | |
| Bezel Material | Plastic | |

Complementary

| Switching Angle | 90 ° |
|---|--|
| [Ui] Rated Insulation Voltage | 690 V 3)IEC 60947-1 |
| [Ithe] Conventional Enclosed Thermal Current | 16 A |
| Rated Operational Power In W | 1300 W AC-3, 230 V 1 phase IEC 947-3 14000 W AC-21, 400 V 3 phase IEC 947-3 17000 W AC-21, 500 - 660 V 3 phase IEC 947-3 2200 W AC-3, 230 V 3 phase IEC 947-3 2200 W AC-3, 400 V 1 phase IEC 947-3 4000 W AC-23A, 230 V 3 phase IEC 947-3 4000 W AC-3, 400 V 3 phase IEC 947-3 4000 W AC-3, 500 V 3 phase IEC 947-3 4000 W AC-3, 500 V 3 phase IEC 947-3 5500 W AC-23A, 400 V 3 phase IEC 947-3 5500 W AC-23A, 500 V 3 phase IEC 947-3 5500 W AC-23A, 500 V 3 phase IEC 947-3 5500 W AC-23A, 500 V 3 phase IEC 947-3 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| [le] Rated Operational Current Ac | 8 A 400 V AC-3 3 phase IEC 947-3 10.8 A 400 V AC-23A 3 phase IEC 947-3 14.6 A 230 V AC-23A 3 phase IEC 947-3 4.7 A 690 V AC-3 3 phase IEC 947-3 6.4 A 690 V AC-23A 3 phase IEC 947-3 6.5 A 500 V AC-3 3 phase IEC 947-3 8.3 A 230 V AC-3 3 phase IEC 947-3 8.9 A 500 V AC-23A 3 phase IEC 947-3 2 A 500 V AC-15 IEC 947-5-1 3 A 400 V AC-15 IEC 947-5-1 4 A 230 V AC-15 IEC 947-5-1 | |
|--|---|--|
| Electrical Durability | 200000 cycles AC-23 200000 cycles AC-3 600000 cycles AC-15 600000 cycles AC-21 | |
| Maximum Operating Rate | 2.5 cyc/mn AC-21 2.5 cyc/mn AC-23 2.5 cyc/mn AC-3 8.333 cyc/mn AC-15 | |
| Short-Circuit Current | 10000 A | |
| Short-Circuit Protection | 20 A cartridge fuse gG | |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV in isolating function 6 kV IEC 947-1 | |
| Contact Operation | Slow-break | |
| Positive Opening | With | |
| Electrical Connection | Captive screw clamp terminals flexible 2 x 1.5 mm ² Captive screw clamp terminals solid 1 x 2.5 mm ² | |
| Mechanical Durability | 1000000 cycles | |
| Net Weight | 0.23 lb(US) (0.105 kg) | |

Environment

| Standards | IEC 60947-3 power circuit IEC 60947-5-1 control circuit CENELEC EN 50013 | |
|---------------------------------------|---|--|
| Product Certifications | CSA 240 V 3 hp 3 phase 2 UL 240 V 0.33 hp 1 phase 2 CSA 240 V 1 hp 1 phase UL 240 V 1 hp 3 phase | |
| Protective Treatment | TC | |
| Ambient Air Temperature For Operation | -13131 °F (-2555 °C) | |
| Ambient Air Temperature For Storage | -40158 °F (-4070 °C) | |
| Shock Resistance | 30 gn IEC 68-2-27 | |
| Vibration Resistance | 5 gn 10150 Hz)IEC 68-2-6 | |
| Overvoltage Category | Class II IEC 536 Class II NF C 20-030 | |

Ordering and shipping details

| Category | US10CS218406 | |
|-------------------|---------------|--|
| Discount Schedule | 0CS2 | |
| Gtin | 3389110446708 | |
| Returnability | No | |
| Country Of Origin | CZ | |

Packing Units

| • | |
|------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.56 in (6.5 cm) |
| Package 1 Width | 2.56 in (6.5 cm) |
| Package 1 Length | 3.15 in (8.0 cm) |
| Package 1 Weight | 4.44 oz (126.0 g) |
| Unit Type Of Package 2 | S01 |
| Number Of Units In Package 2 | 16 |
| Package 2 Height | 5.91 in (15.0 cm) |
| Package 2 Width | 5.91 in (15.0 cm) |
| Package 2 Length | 15.75 in (40.0 cm) |
| Package 2 Weight | 4.87 lb(US) (2.208 kg) |

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ② | Toxic Heavy Metal Free | |
| ② | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | No need of specific recycling operations |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |