

Product data sheet

Specifications



Cam switch, Harmony K, front mounting, plastic, 3 poles, 2 positions, 60°, 32A, 64x64mm, marked 0/1

K30C003AP

❗ Discontinued

❗ Discontinued on: Mar 8, 2023

Main

Range Of Product	Harmony K
Product Or Component Type	Complete cam switch
Component Name	K30
[Ith] Conventional Free Air Thermal Current	32 A
Product Mounting	Front mounting
Fixing Mode	4 holes
Cam Switch Head Type	With front plate 64 x 64 mm
Type Of Operator	Black handle
Rotary Handle Padlocking	Without
Presentation Of Legend	With metallic, 0 - 1 black
Cam Switch Function	Switch
Return	Without
Off Position	With Off position
Poles Description	3P
Switching Positions	Right: 0° - 60°
Ip Degree Of Protection	IP40 conforming to IEC 60529

Complementary

Switching Angle	60 °
[UI] Rated Insulation Voltage	690 V 3)IEC 60947-1
Short-Circuit Current	5000 A
Short-Circuit Protection	50 A cartridge fuse gG
[Uimp] Rated Impulse Withstand Voltage	6 kV EN 947-1 6 kV IEC 947-1
Contact Operation	Slow-break
Positive Opening	With
Electrical Connection	Captive screw clamp terminals flexible 2 x 4 mm² Captive screw clamp terminals solid 2 x 6 mm²
Tightening Torque	10.62 lbf.in (1.2 N.m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Switching Capacity In Ma	11000 mA DC 120 V 2 inductive 50 ms)
	11000 mA DC 180 V 3 inductive 50 ms)
	11000 mA DC 60 V 1 inductive 50 ms)
	1200 mA DC 220 V 1 resistive 1 ms)
	1200 mA DC 440 V 2 resistive 1 ms)
	1200 mA DC 660 V 3 resistive 1 ms)
	16000 mA DC 140 V 3 inductive 50 ms)
	16000 mA DC 48 V 1 inductive 50 ms)
	16000 mA DC 95 V 2 inductive 50 ms)
	23000 mA DC 120 V 2 resistive 1 ms)
	23000 mA DC 180 V 3 resistive 1 ms)
	23000 mA DC 60 V 1 resistive 1 ms)
	25000 mA DC 30 V 1 inductive 50 ms)
	25000 mA DC 60 V 2 inductive 50 ms)
	25000 mA DC 90 V 3 inductive 50 ms)
	3200 mA DC 110 V 1 inductive 50 ms)
	3200 mA DC 220 V 2 inductive 50 ms)
	3200 mA DC 330 V 3 inductive 50 ms)
	32000 mA DC 140 V 3 resistive 1 ms)
	32000 mA DC 24 V 1 inductive 50 ms)
	32000 mA DC 24 V 1 resistive 1 ms)
	32000 mA DC 48 V 1 resistive 1 ms)
	32000 mA DC 48 V 2 inductive 50 ms)
	32000 mA DC 48 V 2 resistive 1 ms)
	32000 mA DC 70 V 3 inductive 50 ms)
	32000 mA DC 70 V 3 resistive 1 ms)
	32000 mA DC 95 V 2 resistive 1 ms)
	400 mA DC 440 V 1 resistive 1 ms)
	400 mA DC 660 V 2 resistive 1 ms)
	6500 mA DC 110 V 1 resistive 1 ms)
	6500 mA DC 220 V 2 resistive 1 ms)
	6500 mA DC 330 V 3 resistive 1 ms)
Mechanical Durability	300000 cycles
Cad Overall Width	2.52 in (64 mm)
Cad Overall Height	2.52 in (64 mm)
Cad Overall Depth	3.66 in (93 mm)
Net Weight	0.49 lb(US) (0.224 kg)

Environment

Standards	IEC 60947-3
Product Certifications	CULus 120 V 2 hp 1 phase CULus 240 V 5 hp 1 phase CULus 240 V 5 hp 3 phase CULus 480 V 20 hp 3 phase
Protective Treatment	TC
Ambient Air Temperature For Operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)
Electrical Shock Protection Class	Class II IEC 60536 Class II NF C 20-030

Ordering and shipping details

Category	21446-9003 K CAM SWITCHES
Discount Schedule	CS1
Gtin	3389110081152
Returnability	No
Country Of Origin	AT

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.83 in (7.2 cm)
Package 1 Width	2.83 in (7.2 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	7.90 oz (224.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	30
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	15.97 lb(US) (7.244 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Reach Free Of Svhc	
 Toxic Heavy Metal Free	
 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Dimensions

Rear Mounting




e support panel thickness 0.5 to 5.5 mm / 0.02 to 0.22 in in.

a		b		c		D1	
mm	in.	mm	in.	mm	in.	mm	in.
53.7	2.11	58	2.28	64	2.52	4.1	0.16

Mounting and Clearance

Panel Cut-Out

Front Mounting




D2		D3		G1	
mm	in.	mm	in.	mm	in.
4.5	0.18	10	0.39	48	1.89

Technical Description

Link Positions (Factory Mounted)


Diagram for 1 to 6-pole Switches

Select the number of poles according to the product characteristics



- I1 Input 1
- I2 Input 2
- O1 Output 1
- O2 Output 2

Marking




Angular Position of Switch



Switching Program

Diagram for 1 to 6-pole Switches

Select the number of poles according to the product characteristics



- (1) 1-pole
- (2) 2-pole
- (3) 3-pole
- (4) 4-pole
- (6) 6-pole

Convention Used for Switching Program Representation

-  Contact closed
-  Contact closed in 2 positions and maintained between the 2 positions
-  Sealed assembly for auto-maintain control
-  Overlapping contacts
-  Spring return position: for a switching angle of 90°, spring return is over 30° after the last position (for a maximum of 3 simultaneous contacts).

Example:

