Product data sheet

Specification





Time delay auxiliary contact block, TeSys Deca, 1NO + 1NC, on delay 10-180s, front, lugs-ring terminals

LADT46

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 157.20 USD

Main

IVIAIII	
Range	TeSys
	TeSys Deca
Product Name	TeSys Deca
Product Or Component Type	Time delay auxiliary contact block
Range Compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F
	TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D
Mounting Location	Front
Pole Contact Composition	1 NO + 1 NC
Contacts Operation	Time delay
Timer Type	On delay
Time Delay Range	10180 s
[Ue] Rated Operational Voltage	690 V AC 25400 Hz
[le] Rated Operational Current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
[Ui] Rated Insulation Voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C))
Standards	UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN/IEC 60947-5-1 UL 60947-5-1
Product Certifications	CB UL CSA CCC UKCA

Complementary

Irms Rated Making Capacity	140 A AC		
	250 A DC		

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Permissible Short-Time Rating	100 A 140 °F (60 °C) 1 s	
	120 A 140 °F (60 °C) 500 ms	
	140 A 140 °F (60 °C) 100 ms	
Protection Type	GG fuse 10 A	
Mechanical Durability	5 Mcycles	
Minimum Switching Current	5 mA	
Minimum Switching Voltage	17 V	
Non-Overlap Time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact	
Insulation Resistance	> 10 MOhm	
Connections - Terminals	lugs-ring terminals 0.31 in (8 mm))	
Tightening Torque	15.05 lbf.in (1.7 N.m) flat Ø 6 mm	
	15.05 lbf.in (1.7 N.m) Philips No 2	
	15.05 lbf.in (1.7 N.m) pozidriv No 2	
Height	1.89 in (48 mm)	
Width	1.73 in (44 mm)	
Depth	2.40 in (61 mm)	
Color	Dark grey	

Environment

Environmental Characteristic	Normal environment
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH IEC 60068
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Ambient Air Temperature For Operation	-40158 °F (-4070 °C)
Operating Altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112
Gtin	3389110821512
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	2.01 in (5.1 cm)
Package 1 Length	2.60 in (6.6 cm)
Package 1 Weight	3.14 oz (89.0 g)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov