Product data sheet

Specifications





TeSys Deca contactor - 3P(3 NO) - AC-3 - <= 440 V 12 A - 440 V AC coil

LC1D126R7

() Discontinued on: Oct 8, 2021

① Discontinued

Main

Table
TeSys
TeSys Deca
Contactor
LC1D
Motor control
Resistive load
AC-1
AC-4
AC-3
3P
Power circuit <= 690 V AC 25400 Hz
Power circuit <= 300 V DC
25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
12 A (at <140 $^{\circ}$ F (60 $^{\circ}$ C)) at <= 440 V AC AC-3 for power circuit
440 V AC 50/60 Hz

Complementary

Motor Power Kw	3 kW at 220230 V AC 50/60 Hz (AC-3)	
	5.5 kW at 380400 V AC 50/60 Hz (AC-3)	
	5.5 kW at 415440 V AC 50/60 Hz (AC-3)	
	7.5 kW at 500 V AC 50/60 Hz (AC-3)	
	7.5 kW at 660690 V AC 50/60 Hz (AC-3)	
	3.7 kW at 400 V AC 50/60 Hz (AC-4)	
Maximum Horse Power Rating	0.5 hp at 115 V AC 50/60 Hz for 1 phase motors	
	2 hp at 230/240 V AC 50/60 Hz for 1 phase motors	
	3 hp at 200/208 V AC 50/60 Hz for 3 phase motors	
	3 hp at 230/240 V AC 50/60 Hz for 3 phase motors	
	7.5 hp at 460/480 V AC 50/60 Hz for 3 phase motors	
	10 hp at 575/600 V AC 50/60 Hz for 3 phase motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air	25 A (at 140 °F (60 °C)) for power circuit	
Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit	
Irms Rated Making Capacity	250 A at 440 V for power circuit conforming to IEC 60947	
	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Icw] Rated Short-Time Withstand Current	105 A 104 °F (40 °C) - 10 s for power circuit
	210 A 104 °F (40 °C) - 1 s for power circuit 30 A 104 °F (40 °C) - 10 min for power circuit
	61 A 104 °F (40 °C) - 1 min for power circuit 100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit
	25 A gG at <= 690 V coordination type 1 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power Dissipation Per Pole	0.36 W AC-3 1.56 W AC-1
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1
	Power circuit 600 V CSA Power circuit 600 V UL
	Signalling circuit 690 V IEC 60947-1
	Signalling circuit 600 V CSA Signalling circuit 600 V UL
Overvoltage Category	
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Electrical Durability	2 Mcycles 12 A AC-3 <= 440 V 0.8 Mcycles 25 A AC-1 <= 440 V
Control Circuit Type	AC 50/60 Hz
Coil Technology	Without built-in suppressor module
Coil Technology Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz
	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz
	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Control Circuit Voltage Limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm)
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm)
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals Tightening Torque	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals Tightening Torque Auxiliary Contact Composition	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 1 NO + 1 NC
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals Tightening Torque Auxiliary Contact Composition Auxiliary Contacts Type	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 1 NO + 1 NC Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Control Circuit Voltage Limits Inrush Power In Va Hold-In Power Consumption In Va Heat Dissipation Operating Time Maximum Operating Rate Connections - Terminals Tightening Torque Auxiliary Contact Composition Auxiliary Contacts Type Signalling Circuit Frequency	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 50/60 Hz 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 23 W at 50/60 Hz 1222 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: lugs-ring terminals - external diameter: 0.31 in (8 mm) Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals flat Ø 8 mm M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 15.05 lbf.in (1.7

Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Plate Rail
Environment	
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product Certifications	GL RINA DNV LROS (Lloyds register of shipping) UL CCC BV CSA GOST
Ip Degree Of Protection	IP20 front face IEC 60529
Protective Treatment	THIEC 60068-2-30
Climatic Withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Operating Altitude	09842.52 ft (03000 m)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)
Height	3.03 in (77 mm)
Width	1.77 in (45 mm)
Depth	3.39 in (86 mm)
Net Weight	0.72 lb(US) (0.325 kg)

Ordering and shipping details

Category	22354-CTR,TESYS D,OPEN,9-38A AC
Discount Schedule	112
Gtin	3389110803280
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.70 in (9.4 cm)
Package 1 Width	3.19 in (8.1 cm)

 Package 1 Length
 2.13 in (5.4 cm)

 Package 1 Weight
 11.50 oz (326 g)

Contractual warranty

Warranty

18 months

4

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov