## Product data sheet

Specification





# TeSys F contactor - 3P (3 NO) - AC-3 - <= 440 V 115 A - coil 110 V DC

LC1F115FD

! Discontinued on: Oct 8, 2021

! Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Resistive load Motor control	
Utilisation Category	AC-4 AC-3 AC-1	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	110 V DC	
[le] Rated Operational Current	200 A (at <104 °F (40 °C)) at <= 440 V AC-1 115 A (at <131 °F (55 °C)) at <= 440 V AC-3	

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	200 A (at 104 °F (40 °C))
Rated Breaking Capacity	920 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1100 A 104 °F (40 °C) - 10 s 640 A 104 °F (40 °C) - 30 s 520 A 104 °F (40 °C) - 1 min 400 A 104 °F (40 °C) - 3 min 320 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	125 A aM at <= 440 V 200 A gG at <= 440 V
Average Impedance	0.37 mOhm - Ith 200 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	15 W AC-1 5 W AC-3
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Motor Power Kw	
	55 kW at 380400 V AC 50/60 Hz (AC-3) 59 kW at 415 V AC 50/60 Hz (AC-3) 59 kW at 440 V AC 50/60 Hz (AC-3) 75 kW at 500 V AC 50/60 Hz (AC-3) 80 kW at 660690 V AC 50/60 Hz (AC-3) 30 kW at 220230 V AC 50/60 Hz (AC-3) 18.5 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Voltage Limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.150.2 Uc 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In W	560 W 68 °F (20 °C))
Hold-In Power Consumption In W	4.5 W 68 °F (20 °C)
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Operating Time	3040 ms closing 3050 ms opening
Connections - Terminals	Power circuit bar 2 20 x 3 mm  Power circuit lugs-ring terminals 1 0.15 in² (95 mm²)  Power circuit connector 1 0.15 in² (95 mm²)  Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end  Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end  Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end  Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end  Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end  Power circuit bolted connection
Tightening Torque	Power circuit 88.51 lbf.in (10 N.m) Control circuit 10.62 lbf.in (1.2 N.m)
Mounting Support	Plate
Heat Dissipation	4.5 W
Standards	EN 60947-1 IEC 60947-1 IEC 60947-4-1 EN 60947-4-1 JIS C8201-4-1
Product Certifications	LROS (Lloyds register of shipping) DNV ABS RINA CCC RMRoS UL CB BV
Product Certifications  Compatibility Code	DNV ABS RINA CCC RMRoS UL CB
	DNV ABS RINA CCC RMRoS UL CB BV
Compatibility Code	DNV ABS RINA CCC RMRoS UL CB BV
Compatibility Code Control Circuit Type	DNV ABS RINA CCC RMRoS UL CB BV
Compatibility Code Control Circuit Type Environment	DNV ABS RINA CCC RMRoS UL CB BV  LC1F  DC standard  IP2X front face with shrouds IEC 60529
Compatibility Code Control Circuit Type  Environment  Ip Degree Of Protection	DNV ABS RINA CCC RMRoS UL CB BV  LC1F  DC standard  IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Compatibility Code Control Circuit Type  Environment Ip Degree Of Protection  Protective Treatment  Ambient Air Temperature For	DNV ABS RINA CCC RMRoS UL CB BV  LC1F  DC standard  IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106  TH

Height	6.38 in (162 mm)
Width	6.43 in (163.3 mm)
Depth	6.73 in (171 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	7.56 lb(US) (3.43 kg)

## Ordering and shipping details

Category	US10I1222331
Discount Schedule	0112
Gtin	3389110383508
Returnability	No
Country Of Origin	CZ

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

### **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov