Product data sheet

Specification





TeSys F contactor - 4P (4 NO) - AC-1 - <= 440 V 400 A - coil 24 V DC

LC1F3304BD

! Discontinued on: Jun 15, 2023

! Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Resistive load	
Utilisation Category	AC-1	
Poles Description	4P	
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	24 V DC	
[le] Rated Operational Current	400 A (at <104 °F (40 °C)) at <= 440 V AC AC-1	

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	400 A (at 104 °F (40 °C))
Rated Breaking Capacity	2640 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	2650 A 104 °F (40 °C) - 10 s 1800 A 104 °F (40 °C) - 30 s 1300 A 104 °F (40 °C) - 1 min 900 A 104 °F (40 °C) - 3 min 750 A 104 °F (40 °C) - 10 min
Associated Fuse Rating	400 A aM at <= 440 V 500 A gG at <= 440 V
Average Impedance	0.28 mOhm - Ith 400 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power Dissipation Per Pole	44 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	4 NO
Control Circuit Voltage Limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.150.2 Uc 131 °F (55 °C))
Mechanical Durability	10 Mcycles
Inrush Power In W	750 W 68 °F (20 °C))

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Hold-In Power Consumption In W	5 W 68 °F (20 °C)
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)
Operating Time	4050 ms closing 4065 ms opening
Connections - Terminals	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid without cable end
	Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid without cable end
	Power circuit lugs-ring terminals 1 0.37 in² (240 mm²) Power circuit bar 2 30 x 5 mm
	Power circuit bolted connection
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) Power circuit 309.78 lbf.in (35 N.m)
Mounting Support	Plate
Heat Dissipation	5 W
Standards	EN 60947-4-1
	EN 60947-1 IEC 60947-1
	JIS C8201-4-1 IEC 60947-4-1
Product Certifications	
Froduct Certifications	BV RINA
	CCC
	CB RMRoS
	LROS (Lloyds register of shipping)
	DNV
	ABS UL
	UKCA
Compatibility Code	LC1F
Control Circuit Type	DC standard
Environment	
Ip Degree Of Protection	IP20 front face with shrouds IEC 60529 IP20 front face with shrouds VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	23131 °F (-555 °C)
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)
Permissible Ambient Air Temperature Around The Device	-40158 °F (-4070 °C)
Height	8.11 in (206 mm)
Width	10.28 in (261 mm)
Depth	8.62 in (219 mm)
Operating Altitude	9842.52 ft (3000 m) without derating
Net Weight	20.94 lb(US) (9.5 kg)

Ordering and shipping details

Category	US10I1222331
Discount Schedule	0112
Gtin	3389118095328
Returnability	No
Country Of Origin	CZ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.04 in (25.5 cm)
Package 1 Width	9.25 in (23.5 cm)
Package 1 Length	11.42 in (29.0 cm)
Package 1 Weight	20.72 lb(US) (9.4 kg)

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov