Product data sheet

Specifications





Contactor, TeSys K, 3P, AC-3, lt or eq to 440V 12 A, 1 NO aux., 24VAC coil

LC1K12105B7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 86.00 USD

Main

| Range | TeSys |
|---------------------------|---------------------------------|
| Product Or Component Type | Contactor |
| Device Short Name | LC1K |
| Device Application | Control |
| Contactor Application | Resistive load Motor control |

Complementary

| Utilisation Category | AC-3 | |
|---|--|--|
| | AC-3e | |
| | AC-1 | |
| | AC-4 | |
| | | |
| Poles Description | 3P | |
| Power Pole Contact Composition | 3 NO | |
| [Ue] Rated Operational Voltage | Power circuit <= 690 V AC <= 400 Hz | |
| | Signalling circuit <= 690 V AC <= 400 Hz | |
| [le] Rated Operational Current | 12 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit | |
| | 12 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit | |
| | 20 A (at <140 °F (60 °C)) at <= 690 V AC AC-1 for power circuit | |
| Control Circuit Type | AC 50/60 Hz | |
| [Uc] Control Circuit Voltage | 24 V AC 50/60 Hz | |
| Motor Power Kw | 3 kW 220230 V AC 50/60 Hz AC-3 | |
| | 5.5 kW 380415 V AC 50/60 Hz AC-3 | |
| | 5.5 kW 440 V AC 50/60 Hz AC-3 | |
| | 4 kW 690 V AC 50/60 Hz AC-3 | |
| | 3 kW 220230 V AC 50/60 Hz AC-3e | |
| | 5.5 kW 380415 V AC 50/60 Hz AC-3e | |
| | 5.5 kW 440 V AC 50/60 Hz AC-3e | |
| | 4 kW 690 V AC 50/60 Hz AC-3e | |
| | 3 kW 220230 V AC 50/60 Hz AC-4 | |
| | 5.5 kW 380415 V AC 50/60 Hz AC-4 | |
| | 5.5 kW 440 V AC 50/60 Hz AC-4 | |
| | 4 kW 690 V AC 50/60 Hz AC-4 | |
| Auxiliary Contact Composition | 1 NO | |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV | |
| Overvoltage Category | III | |
| [Ith] Conventional Free Air | 20 A (at 140 °F (60 °C)) for power circuit | |
| Thermal Current | 10 A (at 122 °F (50 °C)) for signalling circuit | |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Irms Rated Making Capacity | 144 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947 |
|---|--|
| Rated Breaking Capacity | 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947 |
| [Icw] Rated Short-Time Withstand Current | 115 A 122 °F (50 °C) - 1 s for power circuit 105 A 122 °F (50 °C) - 5 s for power circuit 100 A 122 °F (50 °C) - 10 s for power circuit 75 A 122 °F (50 °C) - 30 s for power circuit 55 A 122 °F (50 °C) - 1 min for power circuit 50 A 122 °F (50 °C) - 3 min for power circuit 25 A 122 °F (50 °C) - 3 min for power circuit 80 A - 1 s for signalling circuit 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit |
| Associated Fuse Rating | 25 A gG at <= 440 V for power circuit 25 A aM for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660 |
| Average Impedance | 3 mOhm - Ith 20 A 50 Hz for power circuit |
| [Ui] Rated Insulation Voltage | Power circuit 600 V UL 508 Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-5-1 Signalling circuit 600 V UL 508 Power circuit 600 V CSA C22.2 No 14 Signalling circuit 600 V CSA C22.2 No 14 |
| Insulation Resistance | > 10 MOhm for signalling circuit |
| Inrush Power In Va | 30 VA (at 68 °F (20 °C)) |
| Hold-In Power Consumption In Va | 4.5 VA (at 68 °F (20 °C)) |
| Heat Dissipation | 1.3 W |
| Control Circuit Voltage Limits | Operational: 0.81.15 Uc (at <122 °F (50 °C)) Drop-out: >= 0.20 Uc (at <122 °F (50 °C)) |
| Connections - Terminals | solder pins 0.00 in (0.035 mm)) |
| Maximum Operating Rate | 3600 cyc/h |
| Auxiliary Contacts Type | Instantaneous 1 NO |
| Signalling Circuit Frequency | <= 400 Hz |
| Minimum Switching Current | 5 mA for signalling circuit |
| Minimum Switching Voltage | 17 V for signalling circuit |
| Mounting Support | Printed circuit boards |
| Operating Time | 1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing |
| Safety Reliability Level | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 |
| Non Overlap Distance | 0.02 in (0.5 mm) |
| Mechanical Durability | 10 Mcycles |
| Electrical Durability | 1.3 Mcycles 12 A AC-3 <= 440 V 1.3 Mcycles 12 A AC-3e <= 440 V 0.3 Mcycles 20 A AC-1 <= 690 V 0.02 Mcycles 72 A AC-4 <= 440 V |

| Mechanical Robustness | Shocks contactor closed, on X axis10 Gn for 11 ms IEC 60068-2-27 | |
|-----------------------|--|--|
| | Shocks contactor closed, on Y axis15 Gn for 11 ms IEC 60068-2-27 | |
| | Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 | |
| | Shocks contactor opened, on X axis6 Gn for 11 ms IEC 60068-2-27 | |
| | Shocks contactor opened, on Y axis10 Gn for 11 ms IEC 60068-2-27 | |
| | Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 | |
| | Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 | |
| | Vibrations contactor opened2 Gn, 5300 Hz IEC 60068-2-6 | |
| Height | 2.28 in (58 mm) | |
| Width | 1.77 in (45 mm) | |
| Depth | 2.24 in (57 mm) | |
| | | |

Environment

| Standards | EN/IEC 60947-4-1 GB/T 14048.4 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 |
|--|--|
| Product Certifications | CB Scheme CCC UL CSA EAC CE UKCA |
| Ip Degree Of Protection | IP2X VDE 0106 |
| Protective Treatment | TC IEC 60068 TC DIN 50016 |
| Ambient Air Temperature For Storage | -58176 °F (-5080 °C) |
| Operating Altitude | 6561.68 ft (2000 m) without derating |
| Flame Retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |

Ordering and shipping details

| Category | US10I1222326 |
|-------------------|---------------|
| Discount Schedule | 0112 |
| Gtin | 3389110789775 |
| Returnability | No |
| Country Of Origin | FR |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.60 in (6.6 cm) |
| Package 1 Width | 1.89 in (4.8 cm) |
| Package 1 Length | 2.44 in (6.2 cm) |
| Package 1 Weight | 7.41 oz (210.0 g) |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

| Toxic Heavy Metal Free | |
|----------------------------|-----|
| Mercury Free | |
| Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Compliant |
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| | Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| | |