## **Product data sheet**

Specifications





# Contactor, TeSys K, 3P, AC-3, It or eq to 440V 12 A, 1 NO aux., 200 to 208VAC coil

LC1K1210L7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 86.00 USD

#### Main

| Range                     | TeSys                           |
|---------------------------|---------------------------------|
| Product Or Component Type | Contactor                       |
| Device Short Name         | LC1K                            |
| Device Application        | Control                         |
| Contactor Application     | Motor control<br>Resistive load |

### Complementary

| oompromontary                          |  |
|--|--|
| Utilisation Category                   | AC-3   |
|  | AC-3e  |
|  | AC-1   |
|  | AC-4   |
| Poles Description                      | 3P   |
| Power Pole Contact Composition         | 3 NO   |
| [Ue] Rated Operational Voltage         | Power circuit <= 690 V AC <= 400 Hz                              |
|  | Signalling circuit <= 690 V AC <= 400 Hz                         |
| [le] Rated Operational Current         | 12 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit  |
|  | 12 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit |
|  | 20 A (at <140 °F (60 °C)) at <= 690 V AC AC-1 for power circuit  |
| Control Circuit Type                   | AC 50/60 Hz  |
| [Uc] Control Circuit Voltage           | 200208 V AC 50/60 Hz   |
| Motor Power Kw                         | 3 kW 220230 V AC 50/60 Hz AC-3                                   |
|  | 5.5 kW 380415 V AC 50/60 Hz AC-3                                 |
|  | 5.5 kW 440 V AC 50/60 Hz AC-3                                    |
|  | 4 kW 690 V AC 50/60 Hz AC-3                                      |
|  | 3 kW 220230 V AC 50/60 Hz AC-3e                                  |
|  | 5.5 kW 380415 V AC 50/60 Hz AC-3e                                |
|  | 5.5 kW 440 V AC 50/60 Hz AC-3e                                   |
|  | 4 kW 690 V AC 50/60 Hz AC-3e                                     |
|  | 3 kW 220230 V AC 50/60 Hz AC-4                                   |
|  | 5.5 kW 380415 V AC 50/60 Hz AC-4                                 |
|  | 5.5 kW 440 V AC 50/60 Hz AC-4                                    |
|  | 4 kW 690 V AC 50/60 Hz AC-4                                      |
| <b>Auxiliary Contact Composition</b>   | 1 NO   |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV   |
| Overvoltage Category                   | Ш  |
| [Ith] Conventional Free Air            | 20 A (at 140 °F (60 °C)) for power circuit                       |
| Thermal Current                        | 10 A (at 122 °F (50 °C)) for signalling circuit                  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Irms Rated Making Capacity  | 144 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947   |
|---|--|
| Rated Breaking Capacity   | 110 A at 440 V conforming to IEC 60947   |
|   | 80 A at 500 V conforming to IEC 60947  |
|   | 70 A at 660690 V conforming to IEC 60947   |
| [Icw] Rated Short-Time Withstand Current  | 115 A 122 °F (50 °C) - 1 s for power circuit   |
| Current   | 105 A 122 °F (50 °C) - 5 s for power circuit   |
|   | 100 A 122 °F (50 °C) - 10 s for power circuit<br>75 A 122 °F (50 °C) - 30 s for power circuit  |
|   | 55 A 122 °F (50 °C) - 1 min for power circuit  |
|   | 50 A 122 °F (50 °C) - 3 min for power circuit  |
|   | 25 A 122 °F (50 °C) - >= 15 min for power circuit  |
|   | 80 A - 1 s for signalling circuit  |
|   | 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit   |
| Associated Fuse Rating  | 25 A gG at <= 440 V for power circuit  |
| 710000lated Face Hatting  | 25 A gM for power circuit  |
|   | 10 A gG for signalling circuit conforming to IEC 60947   |
|   | 10 A gG for signalling circuit conforming to VDE 0660  |
| Average Impedance   | 3 mOhm - Ith 20 A 50 Hz for power circuit  |
| [Ui] Rated Insulation Voltage   | Power circuit 600 V UL 508   |
|   | Power circuit 690 V IEC 60947-4-1<br>Signalling circuit 690 V IEC 60947-4-1  |
|   | Signalling circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-5-1  |
|   | Signalling circuit 600 V UL 508  |
|   | Power circuit 600 V CSA C22.2 No 14  |
|   | Signalling circuit 600 V CSA C22.2 No 14   |
| Insulation Resistance   | > 10 MOhm for signalling circuit   |
| Inrush Power In Va  | 30 VA (at 68 °F (20 °C))   |
| Hold-In Power Consumption In Va   | 4.5 VA (at 68 °F (20 °C))  |
| Heat Dissipation  | 1.3 W  |
| Control Circuit Voltage Limits  | Operational: 0.81.15 Uc (at <122 °F (50 °C)) Drop-out: >= 0.20 Uc (at <122 °F (50 °C))   |
| Connections - Terminals   | screw clamp terminals 1 0.000.01 in² (1.54 mm²)solid   |
|   | screw clamp terminals 1 0.000.01 in² (0.754 mm²)flexible without cable end   |
|   | screw clamp terminals 1 0.000.00 in² (0.342.5 mm²)flexible with cable end  |
|   | screw clamp terminals 2 0.000.01 in² (1.54 mm²)solid   |
|   | screw clamp terminals 2 0.000.01 in² (0.754 mm²)flexible without cable end screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end   |
| Maximum Operating Rate  | 3600 cyc/h   |
|   | 5555 55411   |
| Auxiliary Contacts Type   | Instantaneous 1 NO   |
| Auxiliary Contacts Type Signalling Circuit Frequency  | ·  |
|   | Instantaneous 1 NO   |
| Signalling Circuit Frequency  | Instantaneous 1 NO <= 400 Hz   |
| Signalling Circuit Frequency  Minimum Switching Current   | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate   |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  | Instantaneous 1 NO <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit   |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate   |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  Mounting Support  | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  Mounting Support  | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2  1020 ms coil de-energisation and NO opening   |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  Mounting Support  Tightening Torque   | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2  |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  Mounting Support  Tightening Torque   | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2  1020 ms coil de-energisation and NO opening   |
| Signalling Circuit Frequency Minimum Switching Current Minimum Switching Voltage Mounting Support Tightening Torque Operating Time                                | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2  1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing  B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1  |
| Signalling Circuit Frequency  Minimum Switching Current  Minimum Switching Voltage  Mounting Support  Tightening Torque  Operating Time  Safety Reliability Level | Instantaneous 1 NO  <= 400 Hz  5 mA for signalling circuit  17 V for signalling circuit  Plate Rail  7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals flat Ø 6 mm 7.0811.51 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2  1020 ms coil de-energisation and NO opening 1020 ms coil energisation and NO closing  B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 |

| Electrical Durability | 1.3 Mcycles 12 A AC-3 <= 440 V                                   |
|-----------------------|--|
|                       | 1.3 Mcycles 12 A AC-3e <= 440 V                                  |
|                       | 0.3 Mcycles 20 A AC-1 <= 690 V                                   |
|                       | 0.02 Mcycles 72 A AC-4 <= 440 V                                  |
| Mechanical Robustness | Shocks contactor closed, on X axis10 Gn for 11 ms IEC 60068-2-27 |
|                       | Shocks contactor closed, on Y axis15 Gn for 11 ms IEC 60068-2-27 |
|                       | Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 |
|                       | Shocks contactor opened, on X axis6 Gn for 11 ms IEC 60068-2-27  |
|                       | Shocks contactor opened, on Y axis10 Gn for 11 ms IEC 60068-2-27 |
|                       | Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 |
|                       | Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6           |
|                       | Vibrations contactor opened2 Gn, 5300 Hz IEC 60068-2-6           |
| Height                | 2.28 in (58 mm)  |
| Width                 | 1.77 in (45 mm)  |
| Depth                 | 2.24 in (57 mm)  |
| Net Weight            | 0.40 lb(US) (0.18 kg)  |
|                       |  |

## **Environment**

| Standards                           | EN/IEC 60947-4-1<br>GB/T 14048.4<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>JIS C8201-4-1            |
|-------------------------------------|--|
| Product Certifications              | CB Scheme CCC UL CSA EAC CE UKCA   |
| Ip Degree Of Protection             | IP2X VDE 0106  |
| Protective Treatment                | TC IEC 60068<br>TC DIN 50016   |
| Ambient Air Temperature For Storage | -58176 °F (-5080 °C)   |
| Operating Altitude                  | 6561.68 ft (2000 m) without derating   |
| Flame Retardance                    | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |

## Ordering and shipping details

| Category          | US10l1222326  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3389118049833 |
| Returnability     | No            |
| Country Of Origin | FR            |

## **Packing Units**

| Unit Type Of Package 1       | PCE               |
|------------------------------|-------------------|
| Number Of Units In Package 1 | 1                 |
| Package 1 Height             | 2.56 in (6.5 cm)  |
| Package 1 Width              | 2.44 in (6.2 cm)  |
| Package 1 Length             | 1.89 in (4.8 cm)  |
| Package 1 Weight             | 6.38 oz (181.0 g) |

## **Contractual warranty**

Warranty

18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>Ø</b> | Toxic Heavy Metal Free     |     |
| <b>Ø</b> | Mercury Free               |     |
| <b>9</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant   |
|                           | EU RoHS Declaration   |
| China Rohs Regulation     | China RoHS declaration  |
|                           | Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
|                           |   |