Product data sheet

Specification





TeSys Deca reversing contactor - 3P(3 NO) - AC-3 - <= 440 V 115 A - 115 V AC coil

LC2D115FE7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,465.80 USD

Main

Range	TeSys					
Product Name	TeSys Deca					
Product Or Component Type	Reversing contactor					
Device Short Name	LC2D					
Contactor Application	Resistive load Motor control					
Utilisation Category	AC-3 AC-1 AC-3e					
Device Presentation	Preassembled with reversing power busbar					
Poles Description	3P					
Power Pole Contact Composition	3 NO					
[Ue] Rated Operational Voltage	Power circuit <= 1000 V AC 25400 Hz Power circuit <= 300 V DC					
[le] Rated Operational Current	200 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 115 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit					
Motor Power Kw	30 kW at 220230 V AC 50-60 Hz 55 kW at 380400 V AC 50-60 Hz 59 kW at 415 V AC 50-60 Hz 59 kW at 440 V AC 50-60 Hz 75 kW at 500 V AC 50-60 Hz 80 kW at 660690 V AC 50-60 Hz 65 kW at 1000 V AC 50-60 Hz					
Motor Power Hp (UI / Csa)	30 hp at 200/208 V AC 60 Hz for 3 phase motors 40 hp at 230/240 V AC 60 Hz for 3 phase motors 75 hp at 460/480 V AC 60 Hz for 3 phase motors 100 hp at 575/600 V AC 60 Hz for 3 phase motors					
Control Circuit Type	AC 50/60 Hz					
[Uc] Control Circuit Voltage	115 V AC 50/60 Hz					
Auxiliary Contact Composition	1 NO + 1 NC					
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947					
Overvoltage Category	III					
[Ith] Conventional Free Air Thermal Current	200 A (at 140 °F (60 °C)) for power circuit					
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1260 A at 440 V for power circuit conforming to IEC 60947					
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947					

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Icw] Rated Short-Time Withstand Current	250 A 104 °F (40 °C) - 10 min for power circuit 550 A 104 °F (40 °C) - 1 min for power circuit 950 A 104 °F (40 °C) - 10 s for power circuit 1100 A 104 °F (40 °C) - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit					
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit					
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit					
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL Power circuit 1000 V IEC 60947-4-1					
Electrical Durability	0.8 Mcycles 200 A AC-1 <= 440 V 0.95 Mcycles 115 A AC-3 <= 440 V 0.95 Mcycles 115 A AC-3e <= 440 V					
Power Dissipation Per Pole	24 W AC-1 7.9 W AC-3 7.9 W AC-3e					
Front Cover	With					
Interlocking Type	Mechanical Electrical					
Mounting Support	Plate Rail					
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508					
Product Certifications	BV CCC CSA DNV GL RINA UL EAC UKCA					
Connections - Terminals	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end Control circuit screw clamp terminals 1 0.000.00 in² (12.5 mm²)flexible without cable end Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible without cable end Control circuit screw clamp terminals 1 0.000.00 in² (12.5 mm²)flexible with cable end Control circuit screw clamp terminals 1 0.000.00 in² (12.5 mm²)solid without cable end Control circuit screw clamp terminals 1 0.000.00 in² (12.5 mm²)solid without cable end Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)solid without cable end Power circuit connector 1 0.020.19 in² (10120 mm²)flexible without cable end Power circuit connector 2 0.020.08 in² (1050 mm²)flexible with cable end Power circuit connector 1 0.020.19 in² (10120 mm²)flexible with cable end Power circuit connector 1 0.020.19 in² (10120 mm²)flexible with cable end Power circuit connector 1 0.020.19 in² (10120 mm²)flexible with cable end Power circuit connector 1 0.020.19 in² (10120 mm²)flexible with cable end Power circuit connector 2 0.020.08 in² (1050 mm²)flexible with cable end					
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm) Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2					
Operating Time	2050 ms closing 620 ms opening					

Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	8000000 cycles
Maximum Operating Rate	2400 cyc/h 140 °F (60 °C)

Complementary

•					
Coil Technology	Built-in bidirectional peak limiting diode suppressor				
Control Circuit Voltage Limits	0.30.5 Uc 131 °F (55 °C) drop-out AC 50/60 Hz 0.81.15 Uc 131 °F (55 °C) operational AC 50/60 Hz				
Inrush Power In Va	280350 VA 60 Hz 0.8 68 °F (20 °C)) 280350 VA 50 Hz 0.8 68 °F (20 °C))				
Hold-In Power Consumption In Va	218 VA 68 °F (20 °C)) 0.3 60 Hz 218 VA 68 °F (20 °C)) 0.3 50 Hz				
Heat Dissipation	38 W 50/60 Hz				
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1				
Signalling Circuit Frequency	25400 Hz				
Minimum Switching Current	5 mA for signalling circuit				
Minimum Switching Voltage	17 V for signalling circuit				
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact				
Insulation Resistance	> 10 MOhm for signalling circuit				

Environment

Ip Degree Of Protection	IP20 front face IEC 60529				
Climatic Withstand	IACS E10				
Protective Treatment	TH IEC 60068-2-30				
Pollution Degree	3				
Ambient Air Temperature For Operation	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating				
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)				
Operating Altitude	09842.52 ft (03000 m)				
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1				
Flame Retardance	V1 conforming to UL 94				
Mechanical Robustness	Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open6 Gn for 11 ms				
Height	6.22 in (158 mm)				
Width	10.47 in (266 mm)				
Depth	5.83 in (148 mm)				
Net Weight	14.00 lb(US) (6.35 kg)				

Ordering and shipping details

Category	US10l1222354		
Discount Schedule	0112		

Gtin	3389110960587
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.06 in (23.0 cm)
Package 1 Width	12.40 in (31.5 cm)
Package 1 Length	14.57 in (37.0 cm)
Package 1 Weight	14.33 lb(US) (6.5 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance




Certifications & Standards


REACh Declaration					
Compliant with Exemptions					
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.					
Product Environmental Profile					
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.					
End of Life Information					
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov					

LC2D115FE7

Dimensions Drawings

Dimensions





LC2 or 2 x LC1	а	С	e1	e2	G
D115 and D150	266	148	56	18	242/256
c, e1 and e2: including cabling.					

Connections and Schema

Wiring

