# Product data sheet

Specification





# Differential thermal overload relays, TeSys K, 3.7 to 5.5 A, class 10A

LR2K0312

Product availability: Stock - Normally stocked in distribution facility

Price\*: 59.00 USD

#### Main

| Range                               | TeSys  |
|-------------------------------------|--|
| Product Name                        | TeSys LRK  |
| Product Or Component Type           | Differential thermal overload relay  |
| Device Short Name                   | LR2K   |
| Relay Application                   | Motor protection   |
| Product Compatibility               | LC7K<br>LP1K<br>LP4K<br>LC1K   |
| Network Type                        | DC<br>AC   |
| Thermal Overload Class              | Class 10A IEC 60947-4-1  |
| Thermal Protection Adjustment Range | 3.75.5 A   |
| [Ui] Rated Insulation Voltage       | Power circuit 690 V BS 4941 Power circuit 690 V IEC 60947 Power circuit 750 V VDE 0110 group C Power circuit 600 V CSA C22.2 No 14 |

## Complementary

| Network Frequency                              | <= 400 Hz   |
|--|---|
| Mounting Support                               | Under contactor                                       |
|  | Plate, with specific accessories                      |
|  | Rail, with specific accessories                       |
| Auxiliary Contact Composition                  | 1 NO + 1 NC   |
| [Ith] Conventional Free Air<br>Thermal Current | 6 A signalling circuit                                |
| [Ue] Rated Operational Voltage                 | <= 690 V power circuit                                |
|  | 690 V AC AC-15 signalling circuit                     |
|  | 250 V DC DC-13 signalling circuit                     |
| Associated Fuse Rating                         | 6 A gG for signalling circuit conforming to VDE 0660  |
|  | 6 A gG for signalling circuit conforming to IEC 60947 |
| [Uimp] Rated Impulse Withstand Voltage         | 6 kV  |
| Power Dissipation Per Pole                     | 2 W   |
| Phase Failure Sensitivity                      | Yes IEC 60947-4-1                                     |
| Local Signalling                               | Trip indicator Yellow)                                |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Control Type            | Red push-button trip test function Blue push-button stop and manual reset selector switch manual or automatic reset   |
|-------------------------|---|
| Connections - Terminals | screw clamp terminals 1 0.000.01 in² (1.54 mm²)solid screw clamp terminals 2 0.000.01 in² (1.54 mm²)solid screw clamp terminals 1 0.000.01 in² (0.754 mm²)flexible without cable end screw clamp terminals 2 0.000.01 in² (0.754 mm²)flexible without cable end screw clamp terminals 1 0.000.00 in² (0.342.5 mm²)flexible with cable end screw clamp terminals 2 0.000.00 in² (0.341.5 mm²)flexible with cable end |
| Tightening Torque       | 11.51 lbf.in (1.3 N.m) screw clamp terminals Philips No 2<br>11.51 lbf.in (1.3 N.m) screw clamp terminals flat Ø 6 mm<br>11.51 lbf.in (1.3 N.m) screw clamp terminals pozidriv No 2   |
| Height                  | 2.28 in (58 mm)   |
| Width                   | 1.77 in (45 mm)   |
| Depth                   | 2.56 in (65 mm)   |
| Net Weight              | 0.32 lb(US) (0.145 kg)  |

### **Environment**

| Standards                             | IEC 60947<br>VDE 0660<br>BS 4941<br>NF C 63-650   |
|---------------------------------------|---|
| Product Certifications                | UL<br>CSA<br>UKCA   |
| Protective Treatment                  | TC IEC 60068<br>TC DIN 50016  |
| Ip Degree Of Protection               | IP2X conforming to IEC 60529  |
| Ambient Air Temperature For Operation | -4131 °F (-2055 °C) without derating IEC 60947 -22140 °F (-3060 °C) with derating IEC 60947   |
| Ambient Air Temperature For Storage   | -40158 °F (-4070 °C)  |
| Operating Altitude                    | 6561.68 ft (2000 m) without derating  |
| Fire Resistance                       | 1562 °F (850 °C) IEC 60695-2-1  |
| Flame Retardance                      | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102  |
| Mechanical Robustness                 | Shocks NO contact10 Gn for 11 ms IEC 60068-2-27 Shocks NC contact10 Gn for 11 ms IEC 60068-2-27 Vibrations NO contact2 Gn, 5300 Hz IEC 60068-2-6 Vibrations NC contact2 Gn, 5300 Hz IEC 60068-2-6 |

## Ordering and shipping details

| Category          | US10I1222324  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3389110230567 |
| Returnability     | Yes           |
| Country Of Origin | FR            |

## **Packing Units**

| Unit Type Of Package 1       | PCE                |
|------------------------------|--------------------|
| Number Of Units In Package 1 | 1                  |
| Package 1 Height             | 1.97 in (5.000 cm) |

| Package 1 Width              | 2.76 in (7.000 cm)         |
|------------------------------|----------------------------|
| Package 1 Length             | 3.15 in (8.000 cm)         |
| Package 1 Weight             | 5.64 oz (160.000 g)        |
| Unit Type Of Package 2       | S02                        |
| Number Of Units In Package 2 | 41                         |
| Package 2 Height             | 5.91 in (15.000 cm)        |
| Package 2 Width              | 11.81 in (30.000 cm)       |
| Package 2 Length             | 15.75 in (40.000 cm)       |
| Package 2 Weight             | 15.00 lb(US) (6.805 kg)    |
| Unit Type Of Package 3       | P06                        |
| Number Of Units In Package 3 | 656                        |
| Package 3 Height             | 29.53 in (75.000 cm)       |
| Package 3 Width              | 31.50 in (80.000 cm)       |
| Package 3 Length             | 23.62 in (60.000 cm)       |
| Package 3 Weight             | 257.68 lb(US) (116.882 kg) |

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant with Exemptions   |
| China Rohs Regulation     | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.  |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |