## **Product data sheet**

Specification





# TeSys Deca thermal overload relays - 1...1.6 A - class 10A

LR3D06

Product availability: Stock - Normally stocked in distribution facility

Price\*: 60.00 USD

#### Main

| Range                               | TeSys                                   |
|-------------------------------------|---|
|                                     | TeSys Deca                              |
| Product Name                        | TeSys LRD                               |
|                                     | TeSys Deca                              |
| Product Or Component Type           | Non differential thermal overload relay |
| Device Short Name                   | LR3D                                    |
| Relay Application                   | Motor protection                        |
| Product Compatibility               | LC1D09                                  |
|                                     | LC1D18                                  |
|                                     | LC1D38                                  |
|                                     | LC1D12                                  |
|                                     | LC1D32                                  |
|                                     | LC1D25                                  |
| Network Type                        | AC                                      |
|                                     | DC                                      |
| Thermal Overload Class              | Class 10A IEC 60947-4-1                 |
| Thermal Protection Adjustment Range | 11.6 A                                  |
| [Ui] Rated Insulation Voltage       | Power circuit 600 V CSA                 |
|                                     | Power circuit 600 V UL                  |
|                                     | Power circuit 690 V IEC 60947-4-1       |

#### Complementary

| Network Frequency                              | 0400 Hz  |
|--|--|
| Mounting Support                               | Plate, with specific accessories Rail, with specific accessories Under contactor |
| Tripping Threshold                             | 1.14 +/- 0.06 Ir IEC 60947-4-1   |
| Auxiliary Contact Composition                  | 1 NO + 1 NC  |
| [Ith] Conventional Free Air<br>Thermal Current | 5 A signalling circuit   |
| Permissible Current                            | 3 A 120 V AC-15 signalling circuit<br>0.22 A 125 V DC-13 signalling circuit      |
| [Ue] Rated Operational Voltage                 | 690 V AC 0400 Hz power circuit IEC 60947-4-1                                     |
| Associated Fuse Rating                         | 4 A gG for signalling circuit 4 A BS for signalling circuit                      |
| [Uimp] Rated Impulse Withstand Voltage         | 6 kV   |
| Phase Failure Sensitivity                      | Tripping current 130 % of Ir on two phase, the last one at 0                     |
| Control Type                                   | Red push-button stop Blue push-button reset                                      |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Temperature Compensation | -4140 °F (-2060 °C)   |  |
|--------------------------|---|--|
| Connections - Terminals  | Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible without cable end                              |  |
|                          | Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible with cable end        |  |
|                          | Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) solid without cable end        |  |
|                          | Power circuit screw clamp terminals 1 0.000.02 in <sup>2</sup> (1.510 mm <sup>2</sup> ) flexible without cable end      |  |
|                          | Power circuit screw clamp terminals 1 0.000.01 in² (14 mm²) flexible with cable end                                     |  |
|                          | Power circuit screw clamp terminals 1 $0.000.01~\text{in}^2~(16~\text{mm}^2)$ solid without cable end                   |  |
| Tightening Torque        | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals |  |
| Height                   | 2.60 in (66 mm)   |  |
| Width                    | 1.77 in (45 mm)   |  |
| Depth                    | 2.76 in (70 mm)   |  |
| Net Weight               | 0.27 lb(US) (0.124 kg)  |  |

#### **Environment**

| Climatic Withstand                    | IACS E10   |  |
|---------------------------------------|--|--|
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |  |
| Ambient Air Temperature For Operation | -4140 °F (-2060 °C) without derating IEC 60947-4-1   |  |
| Ambient Air Temperature For Storage   | -76158 °F (-6070 °C)   |  |
| Flame Retardance                      | V1 conforming to UL 94   |  |
| Mechanical Robustness                 | Vibrations6 Gn IEC 60068-2-6<br>Shocks15 Gn for 11 ms IEC 60068-2-7  |  |
| Dielectric Strength                   | 1.89 kV 50 Hz IEC 60947-1  |  |
| Standards                             | EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495 |  |
| Product Certifications                | IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA  |  |

## Ordering and shipping details

| Category          | US10I1222347  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3389110346923 |
| Returnability     | Yes           |
| Country Of Origin | FR            |

## **Packing Units**

| •                            |                      |
|------------------------------|----------------------|
| Unit Type Of Package 1       | PCE                  |
| Number Of Units In Package 1 | 1                    |
| Package 1 Height             | 1.93 in (4.9 cm)     |
| Package 1 Width              | 2.99 in (7.6 cm)     |
| Package 1 Length             | 3.46 in (8.8 cm)     |
| Package 1 Weight             | 4.94 oz (140.0 g)    |
| Unit Type Of Package 2       | S02                  |
| Number Of Units In Package 2 | 24                   |
| Package 2 Height             | 5.91 in (15 cm)      |
| Package 2 Width              | 11.81 in (30 cm)     |
| Package 2 Length             | 15.75 in (40 cm)     |
| Package 2 Weight             | 7.94 lb(US) (3.6 kg) |

## **Contractual warranty**

Warranty 18 months

### Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant with Exemptions   |
| China Rohs Regulation     | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.  |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |