Product data sheet

Specification





TeSys LRF - electronic thermal overload relay - 132...220 A - class 10

LR9F5371

! Discontinued on: Jun 15, 2023



Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys	
Product Name	TeSys LRF	
Device Short Name	LR9F	
Product Or Component Type	Electronic thermal overload relay	
Relay Application	Motor protection	
Product Compatibility	LC1F185LC1F265	
Network Type	AC	
Thermal Overload Class	Class 10 IEC 60947-4	
Thermal Protection Adjustment Range	132220 A	

Complementary

•		
Network Frequency	50/60 Hz	
Mounting Support	Direct on contactor Plate	
Tripping Threshold	1.12 +/- 0.06 In tripping IEC 60947-4-1	
Surge Withstand	4 kV IEC 61000-4-5	
Contacts Type And Composition	1 NO + 1 NC	
[Ith] Conventional Free Air Thermal Current	5 A control circuit	
[Ue] Rated Operational Voltage	1000 V AC 50/60 Hz power circuit VDE 0110 group C	
[Ui] Rated Insulation Voltage	Power circuit 1000 V AC IEC 60947-4	
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947-1	
Phase Failure Sensitivity	Tripping in 4 s +/- 20 % IEC 60947-4-1	
Reset	Manual reset on front relay	
Control Type	Dial White full-load current adjustment Test button Red Push-button Red reset Push-button stop	
Local Signalling	Trip indicator	
Temperature Compensation	-4158 °F (-2070 °C)	
Current Consumption	<= 5 mA no-load	
Switching Capacity For Alarm	0150 mA	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<2.5 V closed state	
flexible - with	
solid	
exible -	
kible - with	
kible - without	

Environment

Standards	IEC 60255-17 IEC 60947-4-1 IEC 60255-8 VDE 0660 EN 60947-4-1	
Product Certifications	UL CSA UKCA	
Protective Treatment	TH	
Ip Degree Of Protection	n IP20 conforming to IEC 60529 IP20 conforming to VDE 0106	
Ambient Air Temperature For Operation	-4131 °F (-2055 °C) IEC 60255-8	
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)	
Operating Altitude	<= 6561.68 ft (2000 m) without derating	
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Mechanical Robustness	Shocks13 Gn for 11 ms IEC 60068-2-7 Vibrations 5300 Hz2 GN IEC 60068-2-6	
Dielectric Strength	6 kV 50 Hz IEC 255-5	
Electromagnetic Compatibility	Resistance to electrostatic discharge 6 kV in indirect mode IEC 61000-4-2 Resistance to electrostatic discharge 8 kV in air IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test 10 V/m IEC 61000-4-3 Fast transients immunity test 2 kV IEC 61000-4-4	

Ordering and shipping details

Category	US10I1222334	
Discount Schedule	0112	
Gtin	3389110566017	
Returnability	Yes	
Country Of Origin	FR	

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1	1	
Package 1 Height	5.91 in (15.000 cm)	
Package 1 Width	6.50 in (16.500 cm)	
Package 1 Length	5.12 in (13.000 cm)	
Package 1 Weight	2.28 lb(US) (1.035 kg)	
Unit Type Of Package 2	S04	
Number Of Units In Package 2	11	
Package 2 Height	11.81 in (30 cm)	
Package 2 Width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	
Package 2 Weight	26.52 lb(US) (12.030 kg)	
Unit Type Of Package 3	P06	
Number Of Units In Package 3	44	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	3 Width 23.62 in (60.000 cm)	
Package 3 Length	31.50 in (80.000 cm)	
Package 3 Weight	130.18 lb(US) (59.048 kg)	

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov