Product data sheet

Specification





Motor controller, TeSys T, Motor Management, CANopen, 6 logic inputs, 3 relay logic outputs, 0.4 to 8A, 100 to 240VAC

LTMR08CFM

① To be discontinued

(!) To be discontinued on: Jul 31, 2025

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,125.00 USD

Main

Range	TeSys
Product Name	TeSys T
Device Short Name	LTMR
Product Or Component Type	Motor controller
Device Application	Equipment monitoring and control
Measurement Current	0.48 A
[Us] Rated Supply Voltage	100240 V AC 50/60 Hz
Current Consumption	862.8 mA
Supply Voltage Limits	93.5264 V AC
Communication Port Protocol	CANopen
Bus Type	CANopen ISO 1198 1127 101000 kbit/s, SUB-D 9 4 twisted shielded pairs cable CANopen ISO 1198 1127 101000 kbit/s, terminal block 4 twisted shielded pairs cable

Complementary

[Ui] Rated Insulation Voltage	690 V EN/IEC 60947-1 690 V CSA C22.2 No 14 690 V UL 508
[Uimp] Rated Impulse Withstand Voltage	4 kV supply, inputs and outputs EN/IEC 60947-4-1 6 kV current or voltage measurement circuit EN/IEC 60947-4-1 0.8 kV communication circuit EN/IEC 60947-4-1
Short-Circuit Withstand	100 kA conforming to EN/IEC 60947-4-1
Associated Fuse Rating	4 A gG output 0.5 A gG control circuit
Protection Type	Power factor variation Reverse polarity protection Thermal protection Phase failure Load fluctuation Overload Phase unbalance Thermal overload protection Overload (long time) Locked rotor Earth-leakage protection

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Network And Machine Diagnosis Type	Event recording Trip history information Phase fault and earth fault trip counters Trip context information Waiting time after overload tripping Remaining operating time before overload tripping Running hours counter/operating time Motor control command recording Starting current and time Fault recording
Logic Input Number	6
Input Current	3.1 mA 100 V 7.5 mA 240 V
Current State 0 Guaranteed	Logic input 040 V <= 15 mA 25 ms
Current State 1 Guaranteed	Logic input 79264 V >= 2 mA 25 ms
Maximum Output Switching Frequency	2 Hz
Load Current	5 A 250 V AC logic output 5 A 30 V DC logic output
Permissible Power	480 VA AC-15), le = 2 A, 500000 cycles output) 30 W DC-13), le = 1.25 A, 500000 cycles output)
Maximum Operating Rate	1800 cyc/h
Contacts Type And Composition	1 NO + 1 NC fault signal 3 NO
Metering Type	Temperature Phase current I1, I2, I3 RMS Imbalance current Average current lavg Earth-fault current
Measurement Accuracy	515 % earth fault current internal measurement 1 % voltage 100830 V) 3 % power factor 5 % earth fault current external measurement +/- 30 min/year internal clock 0,02 Temperature 1 % current 5 % active and reactive power
Overvoltage Category	III
Connection Pitch	0.20 in (5.08 mm)
Connections - Terminals	Control circuit connector 1 0.000.00 in² (0.252.5 mm²) AWG 24AWG 14)flexible with cable end Control circuit connector 1 0.000.00 in² (0.22.5 mm²) AWG 24AWG 14)flexible without cable end Control circuit connector 1 0.000.00 in² (0.252.5 mm²) AWG 24AWG 14)flexible without cable end Control circuit connector 1 0.000.00 in² (0.22.5 mm²) AWG 24AWG 14)solid without cable end Control circuit connector 2 0.000.00 in² (0.21 mm²) AWG 24AWG 14)flexible with cable end Control circuit connector 2 0.000.00 in² (0.21.5 mm²) AWG 24AWG 14)flexible without cable end Control circuit connector 2 0.000.00 in² (0.51.5 mm²) AWG 24AWG 14)flexible without cable end Control circuit connector 2 0.000.00 in² (0.51.5 mm²) AWG 24AWG 14)flexible without cable end Control circuit connector 2 0.000.00 in² (0.21 mm²) AWG 24AWG 14)solid without cable end
Tightening Torque	Control circuit 4.435.31 lbf.in (0.50.6 N.m) flat 0.12 in (3 mm)
Pollution Degree	3

Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3
Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4
Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming
to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC
61000-4-11 Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6
Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5
Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5
Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC
61000-4-5 Policy outputs and outputs ourges (common mode), 4 kV, conforming to EN/IEC
Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC 61000-4-5
Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
3.58 in (91 mm)
2.40 in (61 mm)
4.82 in (122.5 mm)
1.17 lb(US) (0.53 kg)
Web server
LTMR
IACS E10
CSA C22.2 No 14
UL 508
EN 60947-4-1 IEC 60947-4-1
BV
GL
EAC
ATEX
KERI
CCC
ABS
C-tick
CSA
DNV UL
RMRoS
NOM
LROS (Lloyds register of shipping)
RINA
12 x 24 hour cycles EN/IEC 60068-2-30
48 h EN/IEC 60070-2-11 TH EN/IEC 60068
1202 °F (650 °C) EN/IEC 60695-2-12
1760 °F (960 °C) UL 94
-4140 °F (-2060 °C)
-40176 °F (-4080 °C)
-40176 °F (-4080 °C) <= 6561.68 ft (2000 m) without derating
<= 6561.68 ft (2000 m) without derating Vibrations mounted on symmetrical rail1 Gn, 5300 Hz EN/IEC 60068-2-6
<= 6561.68 ft (2000 m) without derating Vibrations mounted on symmetrical rail1 Gn, 5300 Hz EN/IEC 60068-2-6 Vibrations plate mounted4 Gn, 5300 Hz EN/IEC 60068-2-6
<= 6561.68 ft (2000 m) without derating Vibrations mounted on symmetrical rail1 Gn, 5300 Hz EN/IEC 60068-2-6

Ordering and shipping details

Category US10I1222338

Discount Schedule	0112
Gtin	3389119404693
Returnability	No
Country Of Origin	SG

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.76 in (7.0 cm)
Package 1 Width	3.94 in (10.0 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	18.24 oz (517.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	10
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	12.21 lb(US) (5.539 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free
Ø	Rohs Exemption Information Yes
Ø	Pvc Free
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information