# Product data sheet

Specifications





Motor controller, TeSys T, Motor Management, CANopen, 6 logic inputs, 3 relay logic outputs, 5 to 100A, 100 to 240VAC

LTMR100CFM

Product availability: Stock - Normally stocked in distribution facility

#### Price\*: 850.00 USD

#### Main

Range	TeSys
Product Name	TeSys T
Device Short Name	LTMR
Product Or Component Type	Motor controller
Device Application	Equipment monitoring and control
Measurement Current	5100 A
[Us] Rated Supply Voltage	100240 V AC 50/60 Hz
Current Consumption	862.8 mA
Supply Voltage Limits	93.5264 V AC
Communication Port Protocol	CANopen
Bus Type	CANopen ISO 1198 1127 101000 kbit/s, SUB-D 9 4 twisted shielded pairs cable CANopen ISO 1198 1127 101000 kbit/s, terminal block 4 twisted shielded pairs cable

### Complementary

[Ui] Rated Insulation Voltage	690 V EN/IEC 60947-1 690 V CSA C22.2 No 14 690 V UL 508
[Uimp] Rated Impulse Withstand Voltage	4 kV supply, inputs and outputs EN/IEC 60947-4-1 6 kV current or voltage measurement circuit EN/IEC 60947-4-1 0.8 kV communication circuit EN/IEC 60947-4-1
Short-Circuit Withstand	100 kA conforming to EN/IEC 60947-4-1
Associated Fuse Rating	4 A gG output 0.5 A gG control circuit
Protection Type	Thermal protection Locked rotor Phase failure Earth-leakage protection Overload (long time) Power factor variation Phase unbalance Load fluctuation Thermal overload protection Reverse polarity protection Overload

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Network And Machine Diagnosis Type	Event recording Trip history information Starting current and time Running hours counter/operating time Motor control command recording Remaining operating time before overload tripping Fault recording Phase fault and earth fault trip counters Waiting time after overload tripping Trip context information
Logic Input Number	6
Input Current	3.1 mA 100 V 7.5 mA 240 V
Current State 0 Guaranteed	Logic input 040 V <= 15 mA 25 ms
Current State 1 Guaranteed	Logic input 79264 V >= 2 mA 25 ms
Maximum Output Switching Frequency	2 Hz
Load Current	5 A 250 V AC logic output 5 A 30 V DC logic output
Permissible Power	480 VA AC-15), le = 2 A, 500000 cycles output) 30 W DC-13), le = 1.25 A, 500000 cycles output)
Maximum Operating Rate	1800 cyc/h
Contacts Type And Composition	1 NO + 1 NC fault signal 3 NO
Metering Type	Earth-fault current Phase current I1, I2, I3 RMS Imbalance current Temperature Average current lavg
Measurement Accuracy	515 % earth fault current internal measurement 1 % voltage 100830 V) 3 % power factor 5 % earth fault current external measurement +/- 30 min/year internal clock 0,02 Temperature 5 % active and reactive power 0,02 current
Overvoltage Category	III
Connection Pitch	0.20 in (5.08 mm)
Connections - Terminals	Control circuit connector 1 0.000.00 in <sup>2</sup> (0.252.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible with cable end Control circuit connector 1 0.000.00 in <sup>2</sup> (0.22.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible without cable end Control circuit connector 1 0.000.00 in <sup>2</sup> (0.252.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible without cable end Control circuit connector 1 0.000.00 in <sup>2</sup> (0.22.5 mm <sup>2</sup> ) AWG 24AWG 14)solid without cable end Control circuit connector 2 0.000.00 in <sup>2</sup> (0.21 mm <sup>2</sup> ) AWG 24AWG 14)flexible with cable end Control circuit connector 2 0.000.00 in <sup>2</sup> (0.21 mm <sup>2</sup> ) AWG 24AWG 14)flexible with cable end Control circuit connector 2 0.000.00 in <sup>2</sup> (0.21.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible without cable end Control circuit connector 2 0.000.00 in <sup>2</sup> (0.21.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible without cable end Control circuit connector 2 0.000.00 in <sup>2</sup> (0.21.5 mm <sup>2</sup> ) AWG 24AWG 14)flexible without cable end
Tightening Torque	Control circuit 4.435.31 lbf.in (0.50.6 N.m) flat 0.12 in (3 mm)
Pollution Degree	3

Electromagnetic Compatibility	Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4 Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC 61000-4-11 Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6 Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
Width	3.58 in (91 mm)
Height	2.40 in (61 mm)
Depth	4.82 in (122.5 mm)
Net Weight	1.17 lb(US) (0.53 kg)
Web Services	Web server
Compatibility Code	LTMR

### Environment

Standards	IEC 60947-4-1 CSA C22.2 No 14 IACS E10 EN 60947-4-1 UL 508
Product Certifications	LROS (Lloyds register of shipping) DNV UL EAC GL CCC BV ABS KERI ATEX NOM RINA RMRoS C-tick CSA
Protective Treatment	12 x 24 hour cycles EN/IEC 60068-2-30 48 h EN/IEC 60070-2-11 TH EN/IEC 60068
Fire Resistance	1202 °F (650 °C) EN/IEC 60695-2-12 1760 °F (960 °C) UL 94
Ambient Air Temperature For Operation	-4140 °F (-2060 °C)
Ambient Air Temperature For Storage	-40176 °F (-4080 °C)
Operating Altitude	<= 6561.68 ft (2000 m) without derating
Mechanical Robustness	Vibrations mounted on symmetrical rail1 Gn, 5300 Hz EN/IEC 60068-2-6 Vibrations plate mounted4 Gn, 5300 Hz EN/IEC 60068-2-6 Shocks half sine wave acceleration15 Gn for 11 ms EN/IEC 60068-2-27
Ip Degree Of Protection	IP20

# Ordering and shipping details

Category

Discount Schedule	0112
Gtin	3389119404730
Returnability	No
Country Of Origin	CN

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.76 in (7.0 cm)
Package 1 Width	3.94 in (10.0 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	18.84 oz (534.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	10
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	12.53 lb(US) (5.685 kg)

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free
Halogen Free Plastic Parts Product

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information