

TeSys F - contactor coil - LX0FH - 48 V DC low consumption

LX0FH055

! Discontinued on: Jul 12, 2021

! Discontinued

Main

Range	TeSys	
Product Or Component Type	Contactor coil	
Device Short Name	LX0FH	
Control Circuit Type	DC low consumption	
[Uc] Control Circuit Voltage	48 V DC	
Average Resistance	5.19 Ohm latching 68 °F (20 °C) 74.26 Ohm unlatching 68 °F (20 °C)	
Product Compatibility	CR1F265	
Operating Time	50100 ms unlatching 4550 ms latching	
Mechanical Durability	1 Mcycles	
Maximum Operating Rate	120 cyc/h 104 °F (40 °C)	

Complementary

Control Circuit Voltage Limits Latching: 0.85...1.1 Uc
Unlatching: 0.85...1.1 Uc

Environment

Net Weight 1.76 lb(US) (0.8 kg)

Ordering and shipping details

Category	18401-WORLD SERVICE PARTS(CTR ACCESS)	
Discount Schedule	CP10	
Gtin	3389110345490	
Returnability	No	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty 18 months

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reac	h Free Of Svhc	
T oxic	Heavy Metal Free	
⊘ Merc	ury Free	
Rohs	Exemption Information	Yes
Eu Rohs D	irective	Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
China Roh	s Regulation	China RoHS declaration