Product data sheet

Specifications





TeSys F - contactor coil - LX1FX - 110...120 V AC 40...400 Hz

LX1FX110

() To be discontinued on: Dec 31, 2028

(!) To be discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 954.00 USD

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX1FX
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F780
Control Circuit Type	AC 40400 Hz
[Uc] Control Circuit Voltage	110120 V AC 40400 Hz
Inductance Of Closed Circuit	0.21 H
Average Resistance	230 Ohm holding 68 °F (20 °C) 4.95 Ohm inrush 68 °F (20 °C)
Operating Time	130230 ms opening 4080 ms closing
Mechanical Durability	5 Mcycles
Maximum Operating Rate	600 cyc/h 131 °F (55 °C)

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C)) Drop-out 0.20.4 Uc 40400 Hz 131 °F (55 °C))
Inrush Power In Va	2100 VA 40400 Hz cos phi 0.9 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	50 VA 40400 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	44 W 40400 Hz

Environment

Ambient Air Temperature For Operation	23131 °F (-555 °C)
Net Weight	6.61 lb(US) (3 kg)

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
Gtin	3389110387018	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	No
Country Of Origin	CZ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.84 in (25.0 cm)
Package 1 Width	7.28 in (18.5 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	6.88 lb(US) (3.122 kg)
Unit Type Of Package 2	S03
Number Of Units In Package 2	2
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	13.97 lb(US) (6.338 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information