# **Product data sheet**

Specifications





# TeSys F - specific contactor coil - 120...127 V AC 40...400 Hz low consumption

LX9FF127

! To be discontinued on: Dec 31, 2028

① To be discontinued

Product availability: Stock - Normally stocked in distribution facility

Price\*: 93.60 USD

### Main

Range	TeSys	
Product Or Component Type	Specific contactor coil	
Device Short Name	LX9FF	
Range Compatibility	TeSys TeSys F LC1F contactor	
Product Compatibility	LC1F150 LC1F115	
Control Circuit Type	AC 40400 Hz low consumption	
[Uc] Control Circuit Voltage	120127 V AC 40400 Hz	
Inductance Of Closed Circuit	2.65 H	
Average Resistance	19 Ohm inrush 68 °F (20 °C) 746 Ohm holding 68 °F (20 °C)	
Operating Time	130 ms opening 35 ms closing	
Mechanical Durability	10 Mcycles	
Maximum Operating Rate	2400 cyc/h 131 °F (55 °C)	

## Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.20.55 Uc 131 °F (55 °C))
Inrush Power In Va	690855 VA 40400 Hz (at 68 °F (20 °C))
Hold-In Power Consumption In Va	6.68.1 VA 40400 Hz (at 68 °F (20 °C))
Heat Dissipation	5.97.2 W

### **Environment**

Ambient Air Temperature For Operation	23131 °F (-555 °C)
Net Weight	0.95 lb(US) (0.43 kg)

# Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112

Price is ��List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Gtin	3389110248418	
Returnability	Yes	
Country Of Origin	ED.	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.91 in (7.4 cm)
Package 1 Width	4.09 in (10.4 cm)
Package 1 Length	7.01 in (17.8 cm)
Package 1 Weight	18.59 oz (527 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	14
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	16.68 lb(US) (7.564 kg)

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information